



Pulse Connect Secure Pulse Policy Secure

REST API Solutions Guide

Pulse Secure, LLC
2700 Zanker Road, Suite 200
San Jose, CA 95134

<https://www.pulsesecure.net>

Pulse Secure assumes no responsibility for any inaccuracies in this document. Pulse Secure reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Pulse Secure or components thereof might be covered by one or more of the following patents that are owned by or licensed to Pulse Secure: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

REST API Solutions Guide

Copyright © 2020, Pulse Secure, LLC. All rights reserved.

Printed in USA.

Revision History

Document Version	Revision Summary
8.1	Updated Profiler REST APIs URL
8.0	Added/Updated the following sections for 9.1R4 release. <ul style="list-style-type: none"> - Getting Active Sessions - Getting System Information - Fetching the User Login Statistics - Health Check Status - VIP Failover - Applying License - Deleting License - Getting License Clients - Getting License Report from License Server - Profiler REST APIs
7.1	Removed the unused header "Postman-Token" from the Guide.
7.0	Updated the "PCS/PPS Configuration Using REST APIs" section with: <ul style="list-style-type: none"> - Export without ESAP and Pulse Client packages API. - Backup/restore binary configuration - Added sample curl commands
6.0	Updated the "PCS/PPS Configuration Using REST APIs" section with IF MAP related REST APIs.
5.1	Updated the "PCS/PPS Configuration Using REST APIs" section with AD and LDAP related REST APIs.
5.0	Updated with "PCS/PPS Configuration Using REST APIs" section.

Contents

REVISION HISTORY	3
OVERVIEW	7
AUTHENTICATION FOR REST APIS	8
Basic Authentication using the HTTP Authorization Header.....	8
Realm-based Authentication (Recommended)	11
SAMPLE GET/POST/PUT/DELETE REQUEST AND RESPONSES IN PCS.....	13
GET API Call: Fetch the Specific User under Local Authentication Server	13
POST API Call: Create User for Existing Local Authentication Server.....	14
PUT API Call: Update Full name field of Specific user	15
DELETE API Call: DELETE Specific User	17
Representing Configuration Resources Using Links	19
SAMPLE GET/POST/PUT/DELETE REQUEST AND RESPONSES IN PPS.....	20
GET API Call: Fetch the Details under Endpoint Policy	20
POST API Call: Create an SRX Enforcer in Infranet Enforcer Connection.....	21
PUT API Call: Update Existing Configuration Where In Initial Location Group is Configured as Guest	23
DELETE API Call: Delete an SNMP Device	24
PCS/PPS CONFIGURATIONS USING REST APIS	26
GETTING ACTIVE SESSIONS.....	27
GETTING PARTICULAR ACTIVE SESSION DETAILS.....	28
DELETING A PARTICULAR ACTIVE SESSION.....	29
DELETING ALL ACTIVE SESSIONS	29
QUERYING SET OF LEASED LICENSES IN THE LICENSE SERVER SYSTEM.....	30
PULLING STATE FROM A LICENSE SERVER ON A LICENSE CLIENT	32
CONFIGURING CERTIFICATES BASED ON CSR WORKFLOW	33
CREATING A CSR FOR A DEVICE CERTIFICATE	37
DELETING DEVICE CERTIFICATE BY ITS SUBJECT NAME.....	38
GETTING SYSTEM INFORMATION	38
REALM-BASED ADMINISTRATOR USER USING ADMINISTRATOR LOCAL AUTHENTICATION SERVER.....	39
REALM-BASED ADMINISTRATOR USER USING AD AUTHENTICATION SERVER.....	39
REALM-BASED ADMINISTRATOR USER USING LDAP AUTHENTICATION SERVER.....	40
REALM-BASED ADMINISTRATOR USER USING RADIUS AUTHENTICATION SERVER.....	40
REALM-BASED ADMINISTRATOR USER FROM A PARTICULAR SOURCE IP	41
REALM-BASED ADMINISTRATOR AUTHORIZATION ROLE MAPPING TO .ADMINISTRATOR ROLE	42
SPECIFYING SESSION VALIDITY FOR REST ADMIN SESSION	43
GETTING ACTIVE DIRECTORY SEARCH GROUPS	44
ADDING SEARCH GROUP TO ACTIVE DIRECTORY	45
UPDATING ACTIVE DIRECTORY GROUP.....	46
DELETING ACTIVE DIRECTORY GROUPS.....	47
GETTING ALL LDAP GROUP LIST.....	47
ADDING GROUPS TO LDAP	48
UPDATING LDAP SOURCE GROUP	49
DELETING LDAP SOURCE GROUP	50
CREATING A CLUSTER.....	51
ADDING A MEMBER TO CLUSTER.....	51


CLUSTER STATUS.....	52
DELETING CLUSTER MEMBER.....	54
HEALTH CHECK STATUS	55
JOINING A CLUSTER	56
VIP FAILOVER.....	56
CONFIGURING IF MAP SERVER.....	57
CONFIGURING IF MAP CLIENT.....	58
CONFIGURING NO IF MAP SERVER	59
GETTING CONFIG WITHOUT PULSE PACKAGES (ESAP AND PULSE CLIENT PACKAGES).....	60
BACKING UP BINARY CONFIGURATION.....	61
RESTORING BINARY CONFIGURATION (IMPORT=NORMAL).....	61
RESTORING BINARY CONFIGURATION (IMPORT=FULL).....	62
PCS-SPECIFIC CONFIGURATIONS USING REST APIS	64
CREATING A VLAN	65
DELETING A VLAN	66
CREATING A USER ROLE.....	66
FETCHING THE USER LOGIN STATISTICS	68
UPDATING THE USER ROLE SETTINGS	69
DELETING A USER ROLE	71
CREATING A USER REALM.....	71
DELETING A USER REALM.....	75
CREATING A RESOURCE PROFILE	75
DELETING A RESOURCE PROFILE	77
CREATING A RESOURCE POLICY.....	78
FETCHING A RESOURCE POLICY.....	79
DELETING A RESOURCE POLICY.....	80
CREATING AN AD AUTHENTICATION SERVER.....	80
DELETING AN AD AUTHENTICATION SERVER	82
CREATING AN LDAP AUTHENTICATION SERVER.....	82
CREATING A RADIUS SERVER	85
MODIFYING RADIUS SERVER DETAILS.....	87
CREATING SIGN-IN-POLICY	88
DELETING SIGN-IN-POLICY.....	89
DISABLING SIGN-IN-URL	89
CREATING A WEB BOOKMARK FOR A ROLE.....	90
REORDERING.....	91
FETCHING THE RESOURCE WITH MULTIPLE IDENTIFIERS	92
UPDATING RESOURCE IDENTIFIED USING MULTIPLE IDENTIFIERS.....	93
UPDATING PASSWORD IN CLEAR TEXT	94
APPLYING AUTHCODE AND DOWNLOADING LICENSES FROM PCLS ON VA-SPE PSA-V.....	95
APPLYING LICENSE	95
DELETING LICENSE.....	96
GETTING LICENSE CLIENTS.....	97
GETTING LICENSE REPORT FROM LICENSE SERVER.....	99
EXPORTING TOTP USERS FROM ONE DEVICE TO ANOTHER DEVICE	102
IMPORTING TOTP USERS FROM ONE DEVICE TO ANOTHER DEVICE	102
SAMPLE ERROR RESPONSES.....	103
400 BAD REQUEST	103
403 Forbidden.....	106
404 NOT FOUND	107
422 UNPROCESSABLE ENTITY.....	108
LIMITATIONS.....	109

PPS-SPECIFIC CONFIGURATIONS USING REST APIS	110
CREATING THE HC POLICY	111
DELETING THE HC POLICY	112
CREATING THE INFRANET ENFORCER	113
DELETING THE INFRANET ENFORCER	113
CREATING A RESOURCE POLICY	114
DELETING A RESOURCE POLICY	114
CREATING A RADIUS CLIENT	115
DELETING A RADIUS CLIENT	115
CREATING A RADIUS ATTRIBUTE POLICY	116
DELETING A RADIUS ATTRIBUTE POLICY	116
CREATING SNMP DEVICE	117
DELETING SNMP DEVICE	118
CREATING SNMP POLICY	118
DELETING SNMP POLICY	120
CREATING DEVICE GROUP - TACACS+	120
DELETING DEVICE GROUP- TACACS+	120
CREATING TACACS+ CLIENT	121
DELETING TACACS+ CLIENT	121
CREATING SHELL POLICIES	122
DELETING SHELL POLICIES	122
CREATING ADMISSION CONTROL CLIENT	123
DELETING ADMISSION CONTROL CLIENT	123
CREATING ADMISSION CONTROL POLICY	123
DELETING ADMISSION CONTROL POLICY	124
PROFILER REST APIS	124
Approving Devices	124
Updating Device Attributes	125

Overview

The REST API provides a standardized method for Next-Gen firewalls, NAC devices, and third-party systems to interact with PCS/PPS. **Representational state transfer (REST)** or RESTful Web services are one way of providing interoperability between computer systems on the Internet. REST-compliant Web services allow requesting systems to access and manipulate textual representations of Web resources using a uniform and predefined set of stateless operations. In a RESTful Web service, requests made to a resource's URI will elicit a response that may be in XML, HTML, JSON or some other defined format. PCS/PPS supports JSON format only.

REST methods determine the HTTP method for manipulating the resources defined in the service operation. The kind of operations available include those predefined by the HTTP verbs GET, POST, PUT, DELETE and so on. The response may confirm that some alteration has been made to the stored resource, and it may provide hypertext links to other related resources or collections of resources. By making use of a stateless protocol and standard operations, REST systems aim for fast performance, reliability, and the ability to grow, by re-using components that can be managed and updated without affecting the system as a whole, even while it is running.

 **Note:** REST API Support for PCS/PPS involves only Configuration APIs. Also, PCS/PPS supports only the GET, POST, PUT and DELETE APIs.

The valid and supported values are described in the **Table 1**.

Table 1: Valid and Supported Values

HTTP Verb	Definition
DELETE	Delete an existing resource.
GET	Retrieve a representation of a resource.
POST	Create a new resource
PUT	Create a new resource to a new URL or modify an existing resource to an existing URL.

The error codes supported are described in the **Table 2**.

Table 2: Error Codes Supported

HTTP Verb	Definition
200 OK	Requesting for resource information successful using GET Resource update successful using PUT
201 Created	Resource creation successful using POST
204 No Content	Deletion of resource successful with no body. Even PUT, POST may return 204 if no errors or warnings seen
400 – Bad Request	Any Request (GET/PUT/POST/DELETE, and so on) is invalid. Example: Incorrect JSON format

HTTP Verb	Definition
401 – Unauthorized	Any REST Call with invalid credentials
403 – Forbidden	REST Call with valid credentials but no permission
404 – Not found	Requested resource in URI does not exist
422 – Unprocessable Entity	Any validation/referential integrity errors that would result in failure of PUT/POST/DELETE request
500 Server Error	When PCS/PPS rest server is not responding

Authentication for REST APIs

Basic authentication using the HTTP authorization header is used to authenticate username/password on the Administrators auth. server. It is expected that the user is already configured in the Administrators auth. server. On a successful login, a random token (api_key) is generated **once** and sent back as a JSON response. Further access to APIs can use this api_key value as username and password as empty in their Authorization header for access.

 **Note:** A new random api_key is generated on a successful login. The user can continue to use this key till the administrator:

- Enables/disables the user account
- Enables/disables the Allow REST API feature for that user

Basic Authentication using the HTTP Authorization Header

Configurations for REST APIs

The configuration of PCS/PPS can be accessed using REST APIs. The PCS/PPS configuration is represented in a json form when accessed using REST APIs. The structure of the JSON representation is very similar to the structure of PCS/PPS XML configuration.

A new admin UI option for users under "Administrators" authserver has been added. REST API authentication would be successful only for those users who have this option enabled.

REST API access can be enabled from Pulse Connect Secure Admin console as shown below or from [Pulse Connect Secure serial console](#).

To enable this check box in Pulse Connect Secure Admin Console:

1. Go to Authentication > Auth. Servers > Administrators > Update Administrator admin1.
2. Select the **Allow access to REST APIs** check box. See figure below.
3. Click Save Changes.

Pulse Secure System **Authentication** Administrators

Auth Servers > Administrators > Update Administrator admin1

Update Administrator admin1

Full Name:

Authenticate using: Administrators

Password:

Confirm Password:

One-time use (disable account after the next successful sign-in)

Allow console access

Allow access to REST APIs This is the new check box added

Enabled

Disabled

Quarantined

Require user to change password at next sign in

Note: You must also configure password management on the [Authentication server Settings](#) with 'Allow users inherit the server's password management capabilities.'

Enabling REST API Access for an Administrator from the Serial Console

REST API access for an administrator user can be enabled during initial configuration and while creating a new administrator user.

During initial provisioning, there are no administrator accounts configured and the system prompts to create a new administrator user. For the option "Do you want to enable REST API access for this administrator (y/n):", enter **y**.

Note: Any characters other than "y" or "n" are invalid responses.

```

~ — ssh shri@10.243.53.143

Internal port configuration completed, proceeding to next step...
-----
Internal NIC: .[OK]
Currently there are no administrators configured...

Please create an administrator user.
Admin username: admindb
Password:
Confirm password:
Do you want to enable REST API access for this administrator (y/n): y

The administrator was successfully created.
-----

```

When creating a new administrator user from the console using the option "2. Create admin username and password", for the option "Do you want to enable REST API access for this administrator (y/n);", enter **y**.

```

~ — ssh shri@10.243.53.143

Current version: 9.0R1 (build 63950)
Rollback version: 8.3R4 (build 60528)
Reset version: 8.1R4.1 (build 37682)

Licensing Hardware ID: 0332MJ0WK0NUP111S
Serial Number: 0332122015100018

Please choose from among the following options:
 0. Start shell
100. mount root rw and start rsync...
101. mount root rw and chpax /home/bin...
102. modify platform code...
103. validate files...
104. Start sshd for debugging ...
105. Manage fault injection scenarios
 1. Network Settings and Tools
 2. Create admin username and password
 3. Display log/status
 4. System Operations
 5. Toggle password protection for the console (Off)
 6. Create a Super Admin session.
 7. System Maintenance
 8. Reset allowed encryption strength for SSL
[Choice: 2

Please create an administrator username and password.
[Admin username: consoleadmin

[Password:
[Confirm password:
[Do you want to enable REST API access for this administrator (y/n): y

The administrator consoleadmin was successfully created.

```

The entire communication is over TLS. An example is explained below:

REQUEST

```

GET /api/v1/auth HTTP/1.1
Host: 10.209.112.106
Authorization: Basic YWRtaW5kYjpkYW5hMTIz
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Type: application/json
Expires: -1
Keep-Alive: timeout=15

{ "api_key": "p5mM1c7RQu81R2NvssLCCZhP05kf0N2ONFeYeLXX6aU=" }

```

Equivalent Curl Command

Note: While using curl command, ensure appropriate server CA certs is installed in the cert store recognized by curl. The sample curl commands provided in this document assumes you have appropriate server CA certs installed.

COMMAND

```
curl -i -u admindb:dana123 -G https://<hostname>/api/v1/auth
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Type: application/json
```

```
{"api_key": "p9/h85ytEmkDzvkGSmQ4z77p6Ya7aLIC42vh0F9CGaQ="}
```

api_key received in response to authentication request should be used as Username with EMPTY password in all future requests. Refer to the examples in [Sample GET/POST/PUT/DELETE Request and Responses in PCS](#).

Realm-based Authentication (Recommended)

Pulse Secure recommends realm-based authentication instead of basic authentication using the HTTPS authorization header.

REQUEST

```
POST /api/v1/realm_auth HTTP/1.1
```

```
Host: 10.209.116.214
```

```
Content-Type: application/json
```

```
Authorization: Basic YWRtaW46ZGFuYTEyMw==
```

```
{  
  "realm": "adminrealm"  
}
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
content-type →application/json
```

```
{  
  "api_key": "NjQzOGU0N2I5MDUyMWZhZW0NmZiMTMxY2U3M2YyM2Q="
```

Authorization header for all future requests should perform Basic Auth using above api_key value as username and password as empty.

REQUEST

```
GET /api/v1/configuration HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
cDVtTWxjN1JRdTgxUjJOdnNzTENDWmhQMDVrZjBOMk9ORmVZZUxYWDZhVT06
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length →283
```

```
Content-Type →application/json
```

```
{  
  "administrators":  
  { "href": "/api/v1/configuration/administrators" }  
  ,  
  "authentication":  
  { "href": "/api/v1/configuration/authentication" }  
  ,  
  "system":  
  { "href": "/api/v1/configuration/system" }  
  ,  
  "users":  
  { "href": "/api/v1/configuration/users" }  
}
```

Sample GET/POST/PUT/DELETE Request and Responses in PCS

Below is a sample of GET/POST/PUT/DELETE request and responses:

GET API Call: Fetch the Specific User under Local Authentication Server

REQUEST

```
GET /api/v1/configuration/authentication/auth-servers/auth-server/Sys-Local/local/users/user/user0001 HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
cDkvaDg1eXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 309
```

```
Content-Type: application/json
```

```
{
  "change-password-at-signin": "false",
  "console-access": "false",
  "enabled": "true",
  "fullname": "user0001",
  "one-time-use": "false",
  "password-encrypted":
  "3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkleQv+DPQZdUrQi5IWPuihJf8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",
  "username": "user0001"
}
```

Equivalent Curl Command

COMMAND

```
curl -i -u p9/h85ytEmkDzvkgSmQ4z77p6Ya7aLIC42vh0F9CGaQ=: -X GET https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-server/System%20Local/local/users/user/user0001
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Type: application/json
```

```
Content-Length: 303
```

```
{
  "change-password-at-signin": "false",
```

```

"console-access": "false",
"enabled": "true",
"fullname": "user0001",
"one-time-use": "false",
"password-encrypted":
"3u+UR6n8AgABAAAAOrKwtwwYUZlizIhEaq54tt550UA39gKEP8AQ7sjr/WTdtPLf36
mpsI5zGWpORVRjEIFAzVOvmxwgXVLBEJnIRQ==",
"username": "user0001"
}

```

POST API Call: Create User for Existing Local Authentication Server

REQUEST

```

POST /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user HTTP/1.1

```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
cDkvaDg1eXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06
```

```
Content-Type: application/json
```

```

{
  "change-password-at-signin": "false",
  "console-access": "false",
  "enabled": "true",
  "fullname": "user0001",
  "one-time-use": "false",
  "password-encrypted":
  "3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkleQv+DPQZdUrQi5IWPuihJ
  f8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",
  "username": "user0001"
}

```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 122
```

```
Content-Type: application/json
```

```

{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or error!"
      }
    ]
  }
}

```

```

    }
  ]
}
}

```

Equivalent Curl Command

COMMAND

```

curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X POST
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user -H 'Content-Type:
application/json' -d '{"change-password-at-signin": "false", "console-
access": "false", "enabled": "true", "fullname": "user0001", "one-time-
use": "false", "password-cleartext": "abc123", "username": "user0002"}'

```

RESPONSE

HTTP/1.1 201 CREATED

Content-Type: application/json

Content-Length: 128

```

{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}

```

PUT API Call: Update Full name field of Specific user

REQUEST

```

PUT /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user/user0001/fullname HTTP/1.1

```

Host: 10.209.112.106

Authorization: Basic

cDkvaDgIeXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

Cache-Control: no-cache

```

{
  "fullname": "REST API test for user0001"
}

```

```

}

RESPONSE

HTTP/1.1 200 OK

Content-Length: 122

Content-Type: application/json

{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or error!"
      }
    ]
  }
}

```

Equivalent Curl Command

```

COMMAND

curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X PUT
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0001/fullname -H 'Content-
Type: application/json' -d '{"fullname": "user0001"}'

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

Content-Length: 124

{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}

```


After updating, fetch the User details and observe the fullname field updated:

REQUEST

```
GET /api/v1/configuration/authentication/auth-servers/auth-server/Sys-Local/local/users/user/user0001 HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
cDkvaDg1eXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length →327
```

```
Content-Type →application/json
```

```
{
  "change-password-at-signin": "false",
  "console-access": "false",
  "enabled": "true",
  "fullname": "REST API test for user0001",
  "one-time-use": "false",
  "password-encrypted":
  "3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkJEQv+DPQZdUrQi5IWPuihJf8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",
  "username": "user0001"
}
```

DELETE API Call: DELETE Specific User**REQUEST**

```
DELETE /api/v1/configuration/authentication/auth-servers/auth-server/Sys-Local/local/users/user/user0001 HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
cDkvaDg1eXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length →122
```

```
Content-Type →application/json
```

```
{
```

```

"result": {
  "info": [
    {
      "message": "Operation succeed without warning or error!"
    }
  ]
}
}

```

Equivalent Curl Command

COMMAND

```

curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X DELETE
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0002/

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Type: application/json
Content-Length: 0

```

After deleting, try to fetch the resource and you would observe 404 response.

REQUEST

```

GET /api/v1/configuration/authentication/auth-servers/auth-
server/Sys-Local/local/users/user/user0001 HTTP/1.1

```

```

Host: 10.209.112.106

```

```

Authorization: Basic

```

```

cDkvaDgleXRFbWtEenZrR1NtUTR6Nzdwn1lhN2FMSUM0MnZoMEY5Q0dhUT06

```

```

Content-Type: application/json

```

```

Cache-Control: no-cache

```

RESPONSE

```

404 NOT FOUND

```

```

Content-Length: 105

```

```

Content-Type: application/json

```

```

{
  "result": {
    "errors": [
      {
        "message": "Resource does not exist."
      }
    ]
  }
}

```

```
    }  
  ]  
}  
}
```

Representing Configuration Resources Using Links

When performing a GET request on a configuration resource, the json response may have "href" attributes to represent smaller resources within.

As an example, "GET /api/v1/configuration" returns:

```
{  
  "users": {  
    "href": "/api/v1/configuration/users"  
  },  
  "system": {  
    "href": "/api/v1/configuration/system"  
  },  
  "authentication": {  
    "href": "/api/v1/configuration/authentication"  
  },  
  "administrators": {  
    "href": "/api/v1/configuration/administrators"  
  }  
}
```

The href values can be used to access smaller resources.

Sample GET/POST/PUT/DELETE Request and Responses in PPS

Below is a sample of GET/POST/PUT/DELETE request and responses:

GET API Call: Fetch the Details under Endpoint Policy

This example shows how to fetch the details under endpoint policy in PPS.

REQUEST

```
GET /api/v1/configuration/uac HTTP/1.1

Host xx.xx.xx.xx

Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06

Content-Type: application/json

{
  "admissionControl": {
    "href": "/api/v1/configuration/uac/admissionControl"
  },
  "host-enforcer": {
    "href": "/api/v1/configuration/uac/host-enforcer"
  },
  "infranet-enforcer": {
    "href": "/api/v1/configuration/uac/infranet-enforcer"
  },
  "mac-address-realms": {
    "href": "/api/v1/configuration/uac/mac-address-realms"
  },
  "network-access": {
    "href": "/api/v1/configuration/uac/network-access"
  },
  "snmpEnforcement": {
    "href": "/api/v1/configuration/uac/snmpEnforcement"
  }
}
```

RESPONSE

```
HTTP/1.1 200 OK

Content-Length: 340

Content-Type: application/json
```

Equivalent Curl Command

COMMAND

```
curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X GET
https://<hostname>/api/v1/configuration/uac
```

RESPONSE

```
HTTP/1.1 200 OK

Content-Type: application/json
```

```

Content-Length: 620

{
  "admissionControl": {
    "href": "/api/v1/configuration/uac/admissionControl"
  },
  "host-enforcer": {
    "href": "/api/v1/configuration/uac/host-enforcer"
  },
  "infranet-enforcer": {
    "href": "/api/v1/configuration/uac/infranet-enforcer"
  },
  "mac-address-realms": {
    "href": "/api/v1/configuration/uac/mac-address-realms"
  },
  "network-access": {
    "href": "/api/v1/configuration/uac/network-access"
  },
  "networkDeviceAdministration": {
    "href": "/api/v1/configuration/uac/networkDeviceAdministration"
  },
  "snmpEnforcement": {
    "href": "/api/v1/configuration/uac/snmpEnforcement"
  }
}

```

POST API Call: Create an SRX Enforcer in Infranet Enforcer Connection

This example shows how to create an SRX Enforcer in Infranet Enforcer connection.

```

REQUEST
POST /api/v1/configuration/uac/infranet-enforcer/connections/infranet-
enforcer/ HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "idp-for-local-sessions-only": "true",
  "junos": {
    "location-group": "- No 802.1X -",
    "password-encrypted":
"3u+UR6n8AgABAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
  },
  "name": "SRX",
  "serial-number": [
    "SJFIOQJI4KNM"
  ],
  "severity-filter": "medium",
  "use-idp": "false"
}

```

```

}
RESPONSE
HTTP/1.1 201 OK
Content-Length: 122
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or
error!"
      }
    ]
  }
}

```

Equivalent Curl Command

```

COMMAND
curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X POST
https://<hostname>/api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer -H 'Content-Type:
application/json' -d '{"idp-for-local-sessions-only": "true", "junos": {
"location-group": "- No 802.1X -", "password-
encrypted": "3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
},"name": "SRX","serial-number": ["SJFIOQJI4KNM"],"severity-filter":
"medium", "use-idp": "false"}'
RESPONSE
HTTP/1.1 201 CREATED

Content-Type: application/json
Content-Length: 124

{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}

```

PUT API Call: Update Existing Configuration Where In Initial Location Group is Configured as Guest

This example updates the existing configuration where in the initial Location Group is configured as "Guest" and then later updated to "Default" Location group.

Before Updating the Location Group

REQUEST

```
GET api/v1/configuration/uac/network-access/radius-clients/radius-client/Radius%20Client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZ1N1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "location-group": "Guest",
  "name": "Radius Client",
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
```

Equivalent Curl Command

COMMAND

```
curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X PUT
https://<hostname>/api/v1/configuration/uac/network-access/radius-clients/radius-client/Radius%20Client -H 'Content-Type: application/json'
-d '{"location-group": "Default","name": "Radius Client"}'
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 124
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

After Updating the Location Group

REQUEST

```

PUT api/v1/configuration/uac/network-access/radius-clients/radius-
client/Radius%20Client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "location-group": "Default",
  "name": "Radius Client",
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or
error!"
      }
    ]
  }
}

```

DELETE API Call: Delete an SNMP Device

This example shows how to delete SNMP device from PPS.

REQUEST

```

DELETE api/v1/configuration/uac/snmpEnforcement/clients/client/ruckus
HTTP/1.1
Host 10.96.73.37
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```


Equivalent Curl Command

COMMAND

```
curl -I -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X DELETE  
https://<hostname>/api/v1/configuration/uac/snmpEnforcement/clients/client/ruckus
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT  
Content-Type: application/json  
Content-Length: 0
```

PCS/PPS Configurations Using REST APIs

- [Getting Active Sessions](#)
- [Getting Particular Active Session Details](#)
- [Deleting a Particular Active Session](#)
- [Deleting All Active Sessions](#)
- [Querying Set of Leased Licenses in the License Server System](#)
- [Pulling State from a License Server on a License Client](#)
- [Configuring Certificates based on CSR Workflow](#)
- [Creating a CSR for a Device Certificate](#)
- [Deleting Device Certificate by Its Subject Name](#)
- [Getting System Information](#)
- [Realm-based Administrator User Using Administrator Local Authentication Server](#)
- [Realm-based Administrator User Using AD Authentication Server](#)
- [Realm-based Administrator User Using LDAP Authentication Server](#)
- [Realm-based Administrator User Using Radius Authentication Server](#)
- [Realm-based Administrator User from a Particular Source IP](#)
- [Realm-based Administrator Authorization Role Mapping to .Administrator Role](#)
- [Specifying Session Validity for REST Admin Session](#)
- [Getting Active Directory Search Groups](#)
- [Adding Search Group to Active Directory](#)
- [Updating Active Directory Group](#)
- [Deleting Active Directory Groups](#)
- [Getting All LDAP Group List](#)
- [Adding Groups to LDAP](#)
- [Updating LDAP Source Group](#)
- [Deleting LDAP Source Group](#)
- [Creating a Cluster](#)
- [Adding a Member to Cluster](#)
- [Cluster Status](#)
- [Deleting Cluster Member](#)
- [Health Check Status](#)
- [Joining a Cluster](#)
- [VIP Failover](#)
- [Configuring IF MAP Server](#)
- [Configuring IF MAP Client](#)
- [Configuring No IF MAP Server](#)
- [Getting Config Without Pulse Packages \(ESAP and Pulse Client Packages\)](#)
- [Backing Up Binary Configuration](#)
- [Restoring Binary Configuration \(import=normal\)](#)
- [Restoring Binary Configuration \(import=full\)](#)

Getting Active Sessions

REQUEST

```
GET /api/v1/system/active-users HTTP/1.1
```

```
Host: 10.209.114.225
```

```
Authorization: Basic
```

```
QXNzN1FMN3VYdTJlaHpMZTF5QjRBQTdoM1lNa3Q0NXRkc2dHc0hoNzU3Yz06
```

```
Content-Type: application/json
```

RESPONSE

```
Content-Type: application/json
```

```
{
  "active-users": {
    "active-user-records": {
      "active-user-record": [
        {
          "active-user-name": "user1",
          "agent-type": "Windows 8.1 Google Chrome",
          "authentication-realm": "localrealm",
          "endpoint-security-status": "Not Applicable\nPassed
Policies: \nFailed Policies: \nEliminated Roles: ",
          "events": 0,
          "login-node": "localhost2",
          "network-connect-ip": null,
          "network-connect-transport-mode": null,
          "session-id":
"sidb03b1e971b7ebel63bb70c966a8ae2b50767aae300000000",
          "pulse-client-version": "9.1.4.1316",
          "user-roles": "localrealm",
          "user-sign-in-time": "2018/08/23 11:45:40"
        },
        {
          "active-user-name": "user2",
          "agent-type": "Windows 7 Google Chrome",
          "authentication-realm": "localrealm",
          "endpoint-security-status": "Not Applicable\nPassed
Policies: \nFailed Policies: \nEliminated Roles: ",
          "events": 0,
          "login-node": "localhost2",
          "network-connect-ip": null,
          "network-connect-transport-mode": null,
```

```

        "session-id":
        "sid68377b6249d24784edfdd07edfe61ee9934b556100000000",
        "user-roles": "localrealm",
        "user-sign-in-time": "2018/08/23 11:46:15"
    }
]
},
"total-matched-record-number": 2,
"total-returned-record-number": 2,
"user-login-permission": true
}
}

```

Getting Particular Active Session Details

REQUEST

```
GET /api/v1/system/active-users?name=user2 HTTP/1.1
```

```
Host: 10.209.114.225
```

```
Authorization: Basic
```

```
QXNzN1FMN3VYdTJlaHpMZTF5QjRBQTD0M1lNa3Q0NXRkc2dHc0hoNzU3Yz06
```

```
Content-Type: application/json
```

RESPONSE

```
Content-Type: application/json
```

```

{
  "active-users": {
    "active-user-records": {
      "active-user-record": [
        {
          "active-user-name": "user2",
          "agent-type": "Windows 7 Google Chrome",
          "authentication-realm": "localrealm",
          "endpoint-security-status": "Not Applicable\nPassed
Policies: \nFailed Policies: \nEliminated Roles: ",
          "events": 0,
          "login-node": "localhost2",
          "network-connect-ip": null,
          "network-connect-transport-mode": null,
          "session-id":
          "sid68377b6249d24784edfdd07edfe61ee9934b556100000000",

```

```

        "user-roles": "localrealm",
        "user-sign-in-time": "2018/08/23 11:46:15"
    }
]
},
"total-matched-record-number": 1,
"total-returned-record-number": 1,
"user-login-permission": true
}
}

```

Deleting a Particular Active Session

REQUEST

```

DELETE /api/v1/system/active-
users/session/sid68377b6249d24784edfdd07edfe61ee9934b556100000000 HTTP/1.1
Host: 10.209.114.225
Authorization: Basic
QXNzN1FMN3VYdTJlaHpMZTF5QjRBQTdoM1lNa3Q0NXRkc2dHc0hoNzU3Yz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Deleting All Active Sessions

REQUEST

```

DELETE /api/v1/system/active-users?all HTTP/1.1
Host: 10.209.114.225
Authorization: Basic
QXNzN1FMN3VYdTJlaHpMZTF5QjRBQTdoM1lNa3Q0NXRkc2dHc0hoNzU3Yz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Querying Set of Leased Licenses in the License Server System

REQUEST

```
GET /api/v1/license/license-server-lease-information HTTP/1.1
Host: 10.209.114.226
Authorization: Basic
c2czWUJmc1lyUjcwN2daSFh6RHdqME1YSnNhddZmcXlaOVZKNFNSdStaZz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 2210
Content-Type: application/json
{
  "leased-license-counts": {
    "features": {
      "feature": [
        {
          "clients": {
            "client-info": [
              {
                "leased-count": 0,
                "name": "client1"
              }
            ]
          },
          "name": "Advanced Mobile License - Onboarding",
          "total-count": 0
        },
        {
          "clients": {
            "client-info": [
              {
                "leased-count": 0,
                "name": "client1"
              }
            ]
          }
        }
      ]
    }
  }
}
```

```
    "name": "Cloud Secure feature",
    "total-count": 0
  },
  {
    "clients": {
      "client-info": [
        {
          "leased-count": 0,
          "name": "client1"
        }
      ]
    },
    "name": "Concurrent Meeting Users",
    "total-count": 0
  },
  {
    "clients": {
      "client-info": [
        {
          "leased-count": 200,
          "name": "client1"
        },
        {
          "leased-count": 0,
          "name": "client2"
        }
      ]
    },
    "name": "Concurrent Users",
    "total-count": 200
  },
  {
    "clients": {
      "client-info": [
        {
          "leased-count": 0,
          "name": "client1"
        }
      ]
    }
  }
]
```

```

    },
    "name": "Named Users",
    "total-count": 0
  },
  {
    "clients": {
      "client-info": [
        {
          "leased-count": 0,
          "name": "client1"
        }
      ]
    },
    "name": "Premier Java Remote Desktop Applet",
    "total-count": 0
  }
]
},
"machine-id": "VASPMVKIT1NJNFPPS",
"query-summary": {},
"release-info": {
  "build-number": "10124",
  "version": "9.0"
},
"serial-number": null,
"signature":
"HMx/W0VhDAABAAApoB/uSUYcwJS1k7HeXVMXK6+KsIPTrJnjXrUci
JEef2EKWYyqgbDGoXhzYaGd16Ye29oOw2KRQlyCM/HRpIpujA==",
"time-stamp": "Fri Aug 24 14:43:00 2018"
}
}

```

Pulling State from a License Server on a License Client

REQUEST

```
PUT /api/v1/license/license-client-lease-state HTTP/1.1
```

```
Host: 10.209.114.228
```

```
Authorization: Basic
```

```
OWZBcVNKUKRCcEdjSEVQY3A0aDZ2UnFwdjhXbExIYzUxRS91TVU1VnBnMD06
```



```
Content-Type: application/json
```

```
{
}
```

Note: While using above URL (i.e., license-client-lease-state) by PUT operation, we provide empty JSON body as input, because PUT operation expects JSON body.

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 86
```

```
Content-Type: application/json
```

```
{
  "result": {
    "info": [
      {
        "message": "Success"
      }
    ]
  }
}
```

Configuring Certificates based on CSR Workflow

REQUEST

```
POST /api/v1/system/certificates/device-certificates HTTP/1.1
```

```
Host: 10.209.114.228
```

```
Authorization: Basic
```

```
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyExubUcyVU5ibz06
```

```
Content-Type: application/json
```

```
{
  "cert" : "MIINzgIBAzCCDYoGCSqGSIB3DQEHAaCCDXsEgg13MIINczCCBg
QGCSqGSIB3DQEHAaCCBfUEggXxMIIF7TCCBekGCyqGSIB
3DQEMCgECOIIE9jCCBPIwHAYKKoZIhvcNAQwBAzA0BAjP
YgwUOJOweAICB9AEggTQFjak4T3ftSlkdoiOtc/xvh
Sfrrkezs109tN6tqyuVYWFQUZkpUIg4v2pU1zOvFOTPlno
VCmeiL2HX7OzuLPALcnSvGmaq61I+Y5dBWMmXMo+bs8s
U36p6YS4D9Bq3VIMecAHwzc/30hPf
+gaaoySQiMuLa34CnNeFxFxMLH0sXi1QeqaLAtMno5AMQW"
```

1/nHSAyJPwa5OWrJ5mkfHKh4kog893diYwo1mlIqlp7Qseza
4+uosWAtih/jac1iDmlb03kjR+OQAukXFQ19ejvyrmMhcjhoz
ARqwMgEj6I+JpdJPUxvwVytQ20Nj4lNDRnAb5sp1oAi0u5aN
49afY6kRjNuKUeUkEmrpmumNJJufkDkKx1eqYOB0qQ50K1w
9qFhEOaOLivGQa1IjzNyc+Bbs2TMw8RJWDsA7TVJhQKBCVjt
IOSFzsVjyWJeI9VzB+iUbi
+XCHYRQP0W6el6HWg2b31iNhMID5Lt2GWQOzT6iUVNls
ZFoofyfxsZBY0JC6nsbvZVMRNBGXE2fEFA/qIga8Gn5E
9zcIqibnXXW0jAOa+m3d+KRR49XaoAjgZpJ3ErqLVz1l/nGTix
9W3H4mSHd9xX43h6Pbz0tGmu6l9nnWP/52y6/TMQQB
5v0RHe0klj+uX00ZuezmmeYEapX+SObQrMqmnvTgWApf
7FzulcvAIHomQ184MJzarNnhOp01AQGESaa6tABtk
2Yzpbm+g5SAgnjwxH0IjeF/kwapQttIYc1TM3qQ9EsPKqbpaQna
4qETIRLI3R6GVNTBnG/g9M9MQh2MtnvonSOlpjDs+Tt
LoO+BtY
9J2XSMK0wtXyONb67xjTRRsC1ulfAvP4RdyHpmM
4JO3+VW1F4n8Vzl+RYrRj0sKja/jHm1ElZvnxJHbwEMFDSv
FIqAvfQGQKyliJWSjalNeO2TEPVJOf2o+TofnYDq4hk0t
ABVdWLRfmn3byi91+xioIOLputEGG8Zto
AdlPkg/lKBnWa37z3eHnfQC9qWU8dcONBQo/HFxupj
482jQa7lUg3fp7apM4CuDQEGJWYNS4/Z+5+zEqq9q+/w
9ke5Y/a/5ukeP9HRS3xpeEe56qb98qP×3dXSSDgXtD1L
6r48Dl+4ISYmLEl0yFwXtJ3vuYk5NiUjmZsuI1tnLQoxim5z6NUZ
5/7G04mG/BzAX3qT74MlRzVda7uZdJPYJLyTGUtidn
562HvYnrGtO9P+08OH6c2Dp4eOgNQCrhPP51ZHd9VNo0nyqt
ZmZ0E4oHN4G7ud+6fwIvaSF9gpwliTWAF5122dr111Ae3ZFPs
5bZv7jrfY7LGuTh+1003MshmtYZAiW8nM1ODm4HstQsSx
HWVb+WK4uiorvhq2cplJ
+71rGQI/kCM8hdZJOUYzsrnQXQUn/rs100w9VAP88SG9mJi
QynoX4+BKYtnn4XE4D3tEFUygD2RmG2GdeGBjOeHh/Ke
MrXk2z9oLEn7CaDeZQCp/7wGdDLfb/nAkmyiO6DWkPZzDAz
GdSDd0gRTkY4LdtyjPTkeADN
+wXvjh6tutjgWgHEHI3xnvMan1/rzZV80SGpbqWFECk1
58YuprYqVRN2CmJCILoVbUaay6Vq9jaHkIkt3lxzU
6UkNTKxqo3Rhad9StfxCRqlrYxgd8wEwYJKoZIHvc
NAQkVMQYEBAEAAAawXQYJKoZIHvcNAQkUMVAeTgBs
AGUALQA2AGMANQA0AGUAMABjADQALQAyAGYANQBkAC0ANABj
AGYAMAAAtAGEAYwBiAGUALQBhADAAyGbjAGUAZgA4AGIAYg
A4AGEAMzBpBgkrBgEEAYI3EQEexXB5aAE0AaQBjAHIAbwBzAG

8AZgB0ACAAUgBTAEAIABTAEMAaABhAG4AbgBlAGw
 AIABDAHIAeQBwAHQAbwBnAHIAYQBwAGgAaQBjACAAUABByAG
 8AdgBpAGQAZQByMI IHZwYJKoZ IhvcNAQcGoIIHWDCCB
 1QCAQAwggdNBgkqhkiG9w0BBwEwHAYKKoZ IhvcNAQw
 BBjAOBAgQOOB7+SpClQICB9CAggcgKOhImrEmUqPOG
 8XR59tFV0HodvnlfzxI7aM6PnAgwPiMSxa6e69kZ/DCeY
 5V5XZkfW+nYAZvgGuZw26oLgVz14T/j0Z3kYTKcn1Mx
 +gvj5coadwFR21HirvwyndeXKJ6w1Yh4omK/x4891AFgv
 KizeeOewczIGmWCqQh81HUgiR8aAfLU2neKxcLoGOfhQnN
 5k/SSKsBTuUBQ80zGiXh+48xS4CTzE8vEyDXyQqE09sqxoDt
 WTW7U5cV8qXwpgy+FSb4c/Y/RCggTqmCL+NwSMCvhEGf
 KSq9ZwJvniEpsQ1mHzK/e4ZRQH/C
 +eNCccV/6zR5onNbZ0fpVTGDCCG0Z9705zzGur5z83CGy
 53fcHS2fdoQP6kqps7VeKbym2NBBT6tx9ZD4Ue988EQwk
 M0dw/7/9resv6VnL+T9prJJq7pEPKyl8ocTSTPbINsSJ
 8f6z+R01/cxOnpyZ3pe2kWneC0xVUeTCsfip5DEbOfga
 Cy4omJstlx57Z5GQrVfs01V21NjY6i0Ev7e2AGyn
 +Kq2ZcrTBzizjQpoA0djljaFodkBVPwROkXCEjScfV/YjURTSgVcv
 1F1k/OyVf3EDcTXzjtOEuvkLrYsBANzAtcchE7tMlJdVlDv
 41A5nudd1plgQkwp911LOM5AieKMGuaSFLCq0RNTho
 61AFTeEOCgK1uDoRtac
 +TtgzrAyQGpUwQ/j/CFzy2yhQzSg2+nOFDA4D2I2Bw
 3SyMVAw45NtPPYnop1Y9j0iRPfSOUzbHqULI8PvRyICY
 3EhIv7MVzG812TMD1WovZzaNonSB4plj+rq+aL6YH1503/AQ
 5v/n3b/ebrKDSSTYROClnVfxxwF+nLTMeCPumAfb8JWd
 AmOvsUmyd8j8b6CgE2fMsR6yzZMmTcdispYe1r
 +at4hd7v57K2JKcTKffs23zU9QZ6w30+soSr4dKhXVko
 Fny8pGZkgA5Dd5ksytKJgKJHM5Z6yRij8cc0WwPrqK
 9jZvFqx0+t8rAFUA1QRbM6nnwF4g6z2vMdEtUYtn
 NXIZIWe5E6YJ1mxzn26dFat2AnM8MelPSNVaxVqho
 CZAZOdRmhYXg4uT
 +4rMazBXJ7txtCNsQd/sW4WpOp9jzRoANfhxK2uKkFRS
 62216u6hCoVCMj5D7UjB/4S80NZIwa67cikY/89t4v
 EZbwvS0dLQ2CMiQVeeUFTto4Hq32RaVRPhIJql0MH/fy
 MIvSfqEoMUnY/D/26rKnivVp9XZdyd2ZKMV5nNFtbw
 C6UhhQ76PwKRG5GsOuDjUxHzy0DXIgtcSuZwUeu
 DNM0iyVZ2LVCRPyTWAiur0nepcn1nVcehlxdddqGSu
 1AWSqmOODMmwytm6mDKAvLnN8qjpL742bTIHkmxt
 UvoNxrgT4i+0jwGWLGNy6sx3JAXIYZv85xt+cV5KDvm

```

F822w6CtUs5l8lWvBdAC6WD
+wmnQzGsqvSbj9jLLKFxOtLYs863dDDtENDZiYtrCKjEKNlo
Y8X0f1N1fczguZ8ssBa6XWQ4hjpgwanpjBsvReJZcWogUFq
YuXtZUB/mIUSZyNSIFwCO4cWa4vqE4P1Pj156jnIdpqwgqalj
HTm7WsCEIbgdBfyJp75/vJR/A4PAJcsZmFfiayNwM/zePFh
Zp0UdxrnoptZfsF4XspgZEPbHyxmfQG7f8sfAQq0iQlH0kpa
BD3VuTrudgOfFbVfrjim8UXUNhKpYSgy3GWeHXadrOHs
OZ0Yj0a/ay5Wwny7RJAZO00UCMLGRVFxYjj9RQvCPphej
NVmhLNqlT3dqEczH3Tptr4xILuoXC6sQkViBhV
7dEp0nVzA6jUzCGOnYmCWi7/N6+bd1XHC6dg
76igIUHHiJz0jqHfIoxqAak+72Iv706QtVMyI+Cpe
4FLRqhoNUJpHAT7+5EOq2WqWXB+KXk5/Wh
7/CIo6pZsAEAU0elDDz/mex2oUfigYvtywFPBo0f
WzTqkWvP7P18E5wudKl9Q+JYoNZVaapChTDJF
9/OoVE1g0rrQ5nxzKQRrTbtekZSJ5j66p107ux2R+Q
7MpRsmwT8ERgW8CexPHOAikAWSBpWaT6ogh
1MletHIK++ShXSIRa3NbDjrwkU8q0E9wlCUyAfXnQv
4pTQaGHadF/j2F2foMBAW2Jgh1KP9UgB54K+KLRjofc
EUqqh+j42bh2/c0jAppJtWNgn2jFQzuK2I3E0MVVNOEPJm
EvpDXM1DZzhFNxeL8D
+Lfmn1B4zNTdngE0arUOspr72Rm0Rx43OcU0w/nkL6DckhvIZdco
4PSLLXJeBW/fBc2Ws04/qxEKwreGwCr3fM17X4HZtCRJOsVj0Bg
6JAp3f30Os55bjQanFubM9YFZrC6rGnKshyiUIFutMPwzbuI
WCWQP29TnlSJWk91C0jb2oy6/209o7U78grLvG11SyyngqehN
8TLxP9MDswHzAHBgUrDgMCGgQU9XDxDBt/loGEHzU/DE
0xAa6823YEFFmEIfAiPtILVXcDNuDn0rU1xc24AgIH0A==" ,
  "password": "juniper",
  "internal-interfaces": { },
  "external-interfaces": { },
  "management-interface": true
}

```

RESPONSE

```

HTTP/1.1 201 OK
Content-Length: 112
Content-Type: application/json
{
  "result": {
    "info": [
      {

```

```

        "message": "Operation successfully completed."
    }
]
}
}

```

Creating a CSR for a Device Certificate

REQUEST

POST /api/v1/system/certificates/device-certificate-csrs HTTP/1.1

Host: 10.209.114.228

Authorization: Basic

aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyExubUcyVU5ibz06

Content-Type: application/json

```

{
  "subject-common-name": "QA.pcs.company.com",
  "key-type": "ECDSA",
  "ecc-curve": "P-384"
}

```

RESPONSE

HTTP/1.1 201 OK

Content-Length: 266

Content-Type: application/json

```

{
  "result": {
    "info": [
      {
        "message": "Created CSR 'CSR_164' successfully"
      },
      {
        "message": "Use POST
/api/v1/system/certificates/device-certificate-
csrs/CSR_164/certificate to upload the signed certificate"
      }
    ]
  }
}

```

Deleting Device Certificate by Its Subject Name

REQUEST

```
DELETE /api/v1/system/certificates/device-
certificates/srikrsa.test.saqacertserv.com HTTP/1.1
```

```
Host: 10.209.114.228
```

```
Authorization: Basic
```

```
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyExubUcyVU5ibz06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

```
Content-Length: 0
```

```
Content-Type: application/json
```

Getting System Information

REQUEST

```
GET /api/v1/system/system-information HTTP/1.1
```

```
Host: 10.209.114.228
```

```
Authorization: Basic
```

```
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyExubUcyVU5ibz06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 193
```

```
Content-Type: application/json
```

```
{
  "rollback-partition-information": {
    "build": "2330",
    "os-name": "ive-sa",
    "os-version": "9.1R2"
  },
  "software-inventory": {
    "software": {
      "build": "4520",
      "name": "IVE-OS",
      "type": "operating-system",
      "version": "9.1R4"
    }
  }
}
```

```

    }
  },
  "system-information": {
    "hardware-model": "PSA5000-V",
    "host-name": "localhost2",
    "os-name": "ive-sa",
    "os-version": "9.1R4",
    "serial-number": "VASPHJPEG824R1U0S"
  }
}

```

Realm-based Administrator User Using Administrator Local Authentication Server

REQUEST

```

POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic YWRtaW4xOmRhbmExMjM=
Content-Type: application/json
{
  "realm": "<realm-name>"
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Type: application/json
{
  "api_key": "MjUwOGQyNzAyOWU3MWQ2MzNiMTM2Njg2MzAwNDg3MjU="
}

```

Realm-based Administrator User Using AD Authentication Server

REQUEST

```

POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic bmF6ZWVyOlBzZW51cmUxMjMk
Content-Type: application/json
{

```

```

    "realm": "AdminADRealm"
  }
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
  "api_key": "ODRjOTcxOTY5ZTlmYTcwY2QwYzk1ZDBjMWQ5N2RmN2Q="
}

```

Realm-based Administrator User Using LDAP Authentication Server

```

REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic bmF6ZWVyOlBzZWV1cmUxMjMk
Content-Type: application/json
{
  "realm": "LDAPRealm"
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
  "api_key": "ZTQxNTIxOTJhNmUwMjg3MmWI5MjZkYmE1MGM0MzdiMDI="
}

```

Realm-based Administrator User Using Radius Authentication Server

```

REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.225
Authorization: Basic amFjazpqcW5pcGVy
Content-Type: application/json
{
  "realm": "RadiusAdminRealm"
}
RESPONSE

```



```

HTTP/1.1 200 OK
Content-Type: application/json
{
  "api_key": "MGMzZjJkZDZlYmRlYzg0MDE5NzkwYzE1ZGM5MmQyYTQ="
}

```

Realm-based Administrator User from a Particular Source IP

REQUEST

```

PUT /api/v1/configuration/administrators/admin-
realms/realm/AdminLocalAuthRealm/authentication-policy/source-
ip/customized HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
T1dFM056VTBPVE15T0dFeU16WXpOakU0WVRFek9EWXhOamRoTVdVNFpqYz06
Content-Type: application/json
{
  "customized": "selected-ip"
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124
Content-Type →application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

REQUEST

```

POST /api/v1/configuration/administrators/admin-
realms/realm/AdminLocalAuthRealm/authentication-policy/source-
ip/ips/ip HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
T1dFM056VTBPVE15T0dFeU16WXpOakU0WVRFek9EWXhOamRoTVdVNFpqYz06

```

```
Content-Type: application/json
{
  "access": "allow",
  "address": "10.96.158.3",
  "netmask": "255.255.255.255"
}
```

RESPONSE

HTTP/1.1 201 CREATED

Content-Length: 124

Content-Type: application/json

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}
```

Realm-based Administrator Authorization Role Mapping to .Administrator Role

REQUEST

```
PUT /api/v1/configuration/administrators/admin-
realms/realm/AdminADRealm/role-mapping-rules HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TldvNF16TmtOVEZqTkRFek1EUXdPVGROt1RrMk9UWTBaR013TkRnM1ptST06
Content-Type: application/json
{
  "user-selects-role": "false",
  "rule": [
    {
      "roles": [
        ".Administrators"
      ],
      "stop-rules-processing": "true",
      "group": {
```

```

        "group-names": [
            "PCS-QA/systems"
        ]
    },
    "name": "AdminADRoleMapping"
}
],
"user-selects-roleset": "false"
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}

```

Specifying Session Validity for REST Admin Session

REQUEST

```

PUT /api/v1/configuration/administrators/admin-roles/admin-
role/%2EAdministrators/general/session-options HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TldVNF16TmtOVEZqTkRFek1EUXdPVGRoTlRrMk9UWTBaR013TkRnM1ptST06
Content-Type: application/json
{
    "idle-timeout": "5"
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124

```

```

Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without
warning or error!"
      }
    ]
  }
}

```

Getting Active Directory Search Groups

REQUEST

```

GET /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 294
Content-Type: application/json
{
  "ad-group": [
    {
      "group": "PCS-QA/core",
      "name": "PCS-QA/core",
      "sid": "S-1-5-21-3875260349-1888520165-453808128-1112"
    },
    {
      "group": "PCS-QA/systems",
      "name": "PCS-QA/systems",
      "sid": "S-1-5-21-3875260349-1888520165-453808128-1108"
    }
  ]
}

```

Adding Search Group to Active Directory

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "ad-group": [
    {
      "group": "PCS-QA/systems",
      "name": "PCS-QA/systems"
    },
    {
      "group": "PCS-QA/core",
      "name": "PCS-QA/core"
    }
  ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

Updating Active Directory Group

NOTE: To update a group, first get already available list using GET operation and append new group to it before PUT.

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVodHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "ad-group": [
    {
      "group": "PCS-QA/core",
      "name": "PCS-QA/core",
      "sid": "S-1-5-21-3875260349-1888520165-453808128-1112"
    },
    {
      "group": "PCS-QA/systems",
      "name": "PCS-QA/systems",
      "sid": "S-1-5-21-3875260349-1888520165-453808128-1108"
    },
    {
      "group": "PCS-QA/client",
      "name": "PCS-QA/client",
      "sid": "S-1-5-21-3875260349-1888520165-453808128-1113"
    }
  ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

```

    }
  ]
}
}

```

Deleting Active Directory Groups

REQUEST

```

PUT /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "ad-group": [
  ]
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Getting All LDAP Group List

REQUEST

```

GET /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1
Host: 10.209.116.192

```

```

Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json

```

Adding Groups to LDAP

REQUEST

```

PUT /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "user-group": [
    {
      "dn": "CN=Administrators,CN=Builtin,DC=pcs-
qa,DC=blrlab,DC=net",
      "group-type": "static",
      "name": "Administrators"
    },
    {
      "dn": "CN=Users,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
      "group-type": "static",
      "name": "Users"
    }
  ]
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```


}

Updating LDAP Source Group

NOTE: To update a group, first get already available list using GET operation and append new group to it and then perform PUT operation.

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-server/LDAPServer/ldap/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVodHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "user-group": [
    {
      "dn": "CN=Administrators,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
      "group-type": "static",
      "name": "Administrators"
    },
    {
      "dn": "CN=Users,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
      "group-type": "static",
      "name": "Users"
    },
    {
      "dn": "CN=Guests,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
      "group-type": "static",
      "name": "Guests"
    }
  ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
```

```

    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Deleting LDAP Source Group

REQUEST

```

PUT /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMesttVzBqL1pKUXh6bz06
Content-Type: application/json
{
  "user-group": [
  ]
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Creating a Cluster

REQUEST

```
PUT /api/v1/cluster HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TldvNF16TmtOVEZqTkrFek1EUXdPVGRoTlRrMk9UWTBaR013TkRnM1ptST06
Content-Type: application/json
{
  "cluster-name": "cluster1",
  "cluster-password": "dana123",
  "member-name": "nodeA",
  "action": "create"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 118
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Created cluster
'cluster1' successfully"
      }
    ]
  }
}
```

Adding a Member to Cluster

REQUEST

```
POST /api/v1/cluster/members HTTP/1.1
Host: 10.209.116.214
Authorization: Basic
THI5bmxreU50UE04MWJ6OHRhbjhFMW1PYTVuV3V5MG5XN0oyNmNWcTRhbz06
Content-Type: application/json
{
  "member-name" : "node225",
}
```

```

"member-ip" : "3.209.114.225",
"member-netmask" : "255.0.0.0",
"member-gateway" : "3.0.0.1",
"member-external-ip" : "2.209.114.225",
"member-external-netmask" : "255.0.0.0",
"member-external-gateway" : "2.0.0.1"
}

```

RESPONSE

HTTP/1.1 200 OK

Content-Length: 125

Content-Type: application/json

```

{
  "result": {
    "info": [
      {
        "message": "Added member 'node225' to cluster
successfully"
      }
    ]
  }
}

```

Cluster Status

REQUEST

GET /api/v1/cluster HTTP/1.1

Host: 10.209.114.228

Authorization: Basic

TWN2cUEzbFRYQXcySjBSbGpKWTazdk1oa2RiTDFLUVJDUjNNdlQ0U1RJdz06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 619

Content-Type: application/json

```

{
  "members": [
    {
      "enabled": true,
      "external-ip": "",

```

```

        "external-network": "",
        "internal-ip": "3.209.114.225",
        "internal-netmask": "255.0.0.0",
        "name": "node225",
        "notes": "Enabled, Unreachable",
        "status-code": "0x18"
    },
    {
        "enabled": true,
        "external-ip": "10.209.114.194",
        "external-network": "255.255.240.0",
        "internal-ip": "3.209.114.228",
        "internal-netmask": "255.0.0.0",
        "name": "nodeA",
        "notes": "Leader",
        "status-code": "0x19004"
    }
],
"mode": "Active/Active",
"name": "cluster1"
}
{
    "external-vip-ipv4": "10.204.56.76",
    "external-vip-owner": "node-51-39",
    "internal-vip-ipv4": "10.204.56.75",
    "internal-vip-owner": "node-51-39",
    "members": [
        {
            "enabled": true,
            "external-ip": "10.204.56.82",
            "external-netmask": "255.255.240.0",
            "internal-ip": "10.204.51.39",
            "internal-netmask": "255.255.240.0",
            "name": "node-51-39",
            "notes": "Leader",
            "status-code": "0x1b004"
        },
        {
            "enabled": true,

```

```

        "external-ip": "10.204.56.87",
        "external-netmask": "255.255.240.0",
        "internal-ip": "10.204.56.88",
        "internal-netmask": "255.255.240.0",
        "name": "Node-something",
        "notes": "Enabled, Unreachable",
        "status-code": "0x18"
    }
],
"mode": "Active/Passive",
"name": "TEST-CLUSTER"
}

```

Deleting Cluster Member

REQUEST

```

DELETE /api/v1/cluster/members/node225 HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TWN2cUEzbfFRYQXcySjBSbGpKWTazdk1oa2RiTDFLUVJDUjNNdlQ0U1RJdz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 129
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Removed member 'node225'
from cluster successfully"
            }
        ]
    }
}

```

Health Check Status

REQUEST

```
GET /api/v1/system/healthcheck
Host: 10.209.114.228
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "message": "Security Gateway is accessible."
}
```

REQUEST

```
GET /api/v1/system/healthcheck?status=all HTTP/1.1
Host: 10.209.114.228
Content-Type: application/json
```

RESPONSE

```
Content-Type: application/json
{
  "CPU-UTILIZATION4": 8,
  "SSL-CONNECTION-COUNT": 0,
  "MAX-LICENSED-USERS-REACHED": "NO",
  "SWAP-UTILIZATION": 1,
  "DISK-UTILIZATION": -1,
  "USER-COUNT": 0,
  "VPN-TUNNEL-COUNT": 0
}
```

REQUEST

```
GET /api/v1/system/healthcheck?status=sbr HTTP/1.1
Host: 10.209.114.228
Content-Type: application/json
```

RESPONSE

```
Content-Type: application/json
{
  "SBR-AVAILABLE": 1
}
```

Joining a Cluster

REQUEST

```
PUT /api/v1/cluster HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
  "cluster-name": "cluster",
  "cluster-password": "dana123",
  "member-address": "3.209.114.225",
  "action": "join"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Joined cluster 'cluster' successfully"
      }
    ]
  }
}
```

VIP Failover

REQUEST

```
PUT /api/v1/cluster
Host: 10.209.114.228
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
  "action": "vip-failover"
}
```


RESPONSE

In case of active-passive cluster:

```
{
  "result": {
    "info": [
      {
        "message": "VIP fail-over initiated"
      }
    ]
  }
}
```

In case of active-active cluster:

```
{
  "result": {
    "info": [
      {
        "message": "Node not part of an Active-Passive cluster.
Invalid operation."
      }
    ]
  }
}
```

Configuring IF MAP Server

REQUEST

```
PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/
```

```
Host: xx.xxx.xxx.xxx
```

```
Authorization: Basic
```

```
SkUyVlBaVjRjcGxleElRMnNiZXPYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
```

```
Content-Type: application/json
```

```
{
  "ifmap-config": " server "
}
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 116
```

```
Content-Type: application/json
```

```
{
```

```

    "result": {
      "info": [
        {
          "message": ": "Operation succeeded without warning or
error!"
        }
      ]
    }
  }
}

```

Configuring IF MAP Client

REQUEST

```

PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/
Host: xx.xxx.xxx.xxx
Authorization: Basic
SkUyVlBaVjRjcGxleElRMnNiZXPYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
  "auth-type": "basic",
    "cert": "None",
    "ifmap-config": "client",
    "password-encrypted":
"3u+UR6n8AgABAAAe9Px2XELrbvvAZACcoOJXBM1051lgG8QQLNR4hcLNrE=",
    "server-url": "https://<PPS-IP-Address>/dana-ws/soap/dsifmap",
    "username": "admin1"
}
{
  "auth-type": "cert",
    "cert": "xx.xxx.xx.xx",
    "ifmap-config": "client",
    "password-encrypted":
"3u+UR6n8AgABAAAe9Px2XELrbvvAZACcoOJXBM1051lgG8QQLNR4hcLNrE=",
    "server-url": "https://<PPS-IP_Address>/dana-ws/soap/dsifmap",
    "username": "admin1"
}

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 116

```

```

Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": ": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Configuring No IF MAP Server

```

REQUEST
PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/
Host: xx.xxx.xxx.xxx
Authorization: Basic
SkUyVlBaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
  "ifmap-config": "no-ifmap"
}

RESPONSE
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": ": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Getting Config Without Pulse Packages (ESAP and Pulse Client Packages)

REQUEST

```
GET /api/v1/configuration/authentication/endpoint/host-
checker/esaps?expand&&excludePulsePackages HTTP/1.1
Host: 10.209.125.139
Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 561
Content-Type: application/json
{
  "active-version": "3.3.5",
  "default-version": "3.3.5",
  "esap": [
    {
      "esap-version": "3.3.5",
      "last-activated-time": "Sun 17 Mar 2019 23:54:12
PDT",
      "upload-time": "Sun 17 Mar 2019 23:53:35 PDT"
    },
    {
      "esap-version": "3.3.6",
      "last-activated-time": "Never",
      "upload-time": "Mon 18 Mar 2019 21:45:31 PDT"
    },
    {
      "esap-version": "3.3.7",
      "last-activated-time": "Never",
      "upload-time": "Mon 18 Mar 2019 21:46:12 PDT"
    }
  ],
  "force-same-esap": "false",
  "opswat-sdk-version": "4"
}
```

Backing Up Binary Configuration

REQUEST

```
GET /api/v1/system/binary-configuration HTTP/1.1
Host: 10.204.51.39
Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: text/html; charset=utf-8
Content-Length: 50753630
UESDBBQAAAAIAE9VmU4J1asqz3cDAKx3AwAKABwAc3lzdGVtLmNmZ1VUCQADvUHB
XL1BwVx1eAsAAQQAAAAABAAAAAAC4D0fwnTMa1OLV2XgACodwMAINEfP2AuIVXV
B1FhtptLC259gyNPT7WwhtQKbp2Y2+dlh1MTflQis8wbHytXP19D+SM+amX5UKeO
GDUggxgbrEQMXmwOSv8YBrvXIBShmGO5BVqfUemvdNK3OB+S/g8+LIPG5i2c3LVm
W8hY3PLQ9CJHMrFSBftgyTX2at85MGCsupxd2gOQQ9e138KrI2hBoywDzCJiRUSU
...
```

Restoring Binary Configuration (import=normal)

The import normal mode will import the binary configuration excluding the IP, network configurations and cluster configuration. The normal mode is similar to default option in binary import.

REQUEST

```
PUT /api/v1/system/binary-configuration?import=normal HTTP/1.1
Or
PUT /api/v1/system/binary-configuration HTTP/1.1
Host: 10.204.51.39
Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
Content-Type: text/html; charset=utf-8
```

RESPONSE

```
HTTP/1.1 200 OK
Error Cases:
import mode specified is incorrect (other than normal or full)
Content-Length: 100
Content-Type: application/json
{
  "result": {
    "errors": [
```

```

    {
      "message": "Invalid import mode"
    }
  ]
}
}

```

Content type is not a base 64 encoded binary configuration string
Content-Length: 126
Content-Type: application/json

```

{
  "result": {
    "errors": [
      {
        "message": "Error - Failed to extract configuration files"
      }
    ]
  }
}

```

Restoring Binary Configuration (import=full)

The import full mode will import everything from the binary configuration provided in the body. This is similar to full binary import.

REQUEST

```

PUT /api/v1/system/binary-configuration?import=full HTTP/1.1
Host: 10.204.51.39
Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
Content-Type: text/html; charset=utf-8
Body data:
Base64 configuration string as received in GET request)

UESDBBQAAAAIAE9VmU4J1asqz3cDAKx3AwAKABwAc3lzdGVtLmNmZ1VUCQADvUHB
XL1BwVx1eAsAAQQAAAAABAAAAAAC4D0fwnTMa1OLV2XgACOdWMAINEfP2AuIVXV
B1FhtptLC259gyNPT7WwhtQKbp2Y2+dlh1MTflQis8wbHytXP19D+SM+amX5UKeO
GDUggxgbrEQMXmwOSv8YBrvXIBShmGO5BVqfUemvdNK3OB+S/g8+LIPG5i2c3LVm
.....

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 112

```

```
Content-Type: application/json
```

```
Error Cases:
```

```
import mode specified is incorrect (other than normal or full)
```

```
Content-Length: 100
```

```
Content-Type: application/json
```

```
{  
  "result": {  
    "errors": [  
      {  
        "message": "Invalid import mode"  
      }  
    ]  
  }  
}
```

```
Content type is not a base 64 encoded binary configuration string
```

```
Content-Length: 126
```

```
Content-Type: application/json
```

```
{  
  "result": {  
    "errors": [  
      {  
        "message": "Error - Failed to extract configuration files"  
      }  
    ]  
  }  
}
```

PCS-Specific Configurations Using REST APIs

- [Creating a VLAN](#)
- [Deleting a VLAN](#)
- [Creating a User Role](#)
- [Fetching the User Login Statistics](#)
- [Updating the User Role Settings](#)
- [Deleting a User Role](#)
- [Creating a User Realm](#)
- [Deleting a User Realm](#)
- [Creating a Resource Profile](#)
- [Deleting a Resource Profile](#)
- [Creating a Resource Policy](#)
- [Fetching a Resource Policy](#)
- [Deleting a Resource Policy](#)
- [Creating an AD Authentication Server](#)
- [Deleting an AD Authentication Server](#)
- [Creating an LDAP Authentication Server](#)
- [Creating a Radius Server](#)
- [Modifying Radius Server Details](#)
- [Creating Sign-In-Policy](#)
- [Deleting Sign-In-Policy](#)
- [Disabling Sign-in-URL](#)
- [Creating a Web Bookmark for a Role](#)
- [Reordering](#)
- [Fetching the Resource with Multiple Identifiers](#)
- [Updating Resource Identified Using Multiple Identifiers](#)
- [Updating Password in Clear Text](#)
- [Applying Authcode and Downloading Licenses from PCLS on VA-SPE | PSA-V](#)
- [Applying License](#)
- [Deleting License](#)
- [Getting License Clients](#)
- [Getting License Report from License Server](#)
- [Exporting TOTP Users from One Device to Another Device](#)
- [Importing TOTP Users from One Device to Another Device](#)
- [Sample Error Responses](#)
- [Limitations](#)

Creating a VLAN

To create a VLAN on a cluster node:

REQUEST

```
POST /api/v1/configuration/system/network/vlans/Node88/vlan/  
HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

```
{  
  "arp-cache": {  
    "arp-entry": []  
  },  
  "name": "vlan-int-1",  
  "routes": {  
    "route": []  
  },  
  "settings": {  
    "default-gateway": "2.0.0.1",  
    "default-vlan-interface": "false",  
    "enable-ipv6": "enabled",  
    "ip-address": "2.2.2.2",  
    "ipv6-address": "fc00:7777:5678:5678::222",  
    "ipv6-default-gateway": "fc00:7777:5678:5678::3",  
    "ipv6-prefix-length": "64",  
    "is-enabled": "enabled",  
    "netmask": "255.0.0.0",  
    "vlan-id": "2",  
    "vlan-parent": "0"  
  },  
  "virtual-ports": {  
    "virtual-port": []  
  }  
}
```

RESPONSE

```

HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}

```

Deleting a VLAN

To delete a VLAN from cluster node:

REQUEST

```

DELETE
/api/v1/configuration/system/network/vlans/Node88/vlan/vlan-int-1
HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json

```

Creating a User Role

To create a user role:

REQUEST

```

POST /api/v1/configuration/users/user-roles/user-role/ HTTP/1.1

```

```
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json
{
  "name": "rest-userrole-4",
  "web": {
    "web-bookmarks": {
      "bookmark": [
        {
          "auto-allow": "disable",
          "description": "",
          "name": "web-bm-1",
          "new-window": "false",
          "no-address-bar": "false",
          "no-tool-bar": "false",
          "parent": "--none--",
          "standard": {
            "url": "http://www.msn.com"
          }
        }
      ]
    },
    "web-options": {
      "browsing-untrusted-sslsites": "true",
      "flash-content": "false",
      "hpxproxy-connection-timeout": "1800",
      "http-connection-timeout": "240",
      "java-applets": "true",
      "mask-hostname": "false",
      "persistent-cookies": "false",
      "rewrite-file-urls": "false",
      "rewrite-links-pdf": "false",
      "unrewritten-page-newwindow": "false",
```

```

        "user-add-bookmarks": "false",
        "user-enter-url": "false",
        "users-bypass-warnings": "false",
        "warn-certificate-issues": "true",
        "websocket-connection-timeout": "900"
    }
}
}

```

RESPONSE

HTTP/1.1 201 CREATED

Content-Length: 122

Content-Type: application/json

```

{
  "result": {
    "info": [
      {
        "message": "Operation succeed
without warning or error!"
      }
    ]
  }
}

```

Fetching the User Login Statistics

To fetch the user login statistics:

REQUEST

GET /api/v1/system/user-stats HTTP/1.1

Host: 10.209.113.88

Authorization: Basic

MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 169

Content-Type: application/json

```
{
```

```

    "user-stats": {
      "allocated-user-count": "25",
      "current-user-count": "0",
      "max-active-user-count-24hrs": "1",
      "min-active-user-count-24hrs": "0"
    }
  }
}

```

Updating the User Role Settings

To update the user role settings:

REQUEST

```

PUT /api/v1/configuration/users/user-roles/user-role/rest-userrole-4 HTTP/1.1

```

```

Host: 10.209.113.88

```

```

Authorization: Basic

```

```

MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

```

```

Content-Type: application/json

```

```

{
  "name": "rest-userrole-4",
  "web": {
    "web-bookmarks": {
      "bookmark": [
        {
          "auto-allow": "disable",
          "description": "",
          "name": "web-bm-1",
          "new-window": "false",
          "no-address-bar": "false",
          "no-tool-bar": "false",
          "parent": "--none--",
          "standard": {
            "url": "http://www.yahoo.com"
          }
        }
      ]
    }
  }
}
]

```



```

    }
}

```

Deleting a User Role

To delete a user role:

REQUEST

```
DELETE /api/v1/configuration/users/user-roles/user-
role/rest-userrole-4 HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

```
Content-Length: 0
```

```
Content-Type: application/json
```

Creating a User Realm

To create a user realm:

REQUEST

```
POST /api/v1/configuration/users/user-realms/realm/ HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

```
{
  "accounting-server": "None",
  "authentication-group": "",
  "authentication-policy": {
    "browser": {
      "customized": "any-user-agent",
      "user-agent-patterns": {
        "user-agent-pattern": []
      }
    }
  }
}
```

```

    },
    "certificate": {
      "cert-key-value-pairs": {
        "cert-key-value-pair": []
      },
      "customized": "allow-all-users"
    },
    "host-checker": {
      "enforce-all-policies": "false",
      "enforce-policy-list": null,
      "evaluate-all-policies": "false",
      "evaluate-logic": "all-policies-must-succeed",
      "evaluate-policy-list": null
    },
    "limits": {
      "guaranteed-minimum": null,
      "limit-concurrent-users": "false",
      "max-sessions-per-user": "1",
      "maximum": null
    },
    "password": {
      "primary-password-expiration-warning-days": "14",
      "primary-password-management": "true",
      "primary-password-minimum-length": "4",
      "primary-password-restricted": "allow-passwords-of-
minimum-length",
      "secondary-password-expiration-warning-days": "14",
      "secondary-password-management": "false",
      "secondary-password-minimum-length": "4",
      "secondary-password-restricted": "allow-passwords-of-
minimum-length"
    },
    "source-ip": {
      "customized": "any-ip",

```



```
        "ips": {
            "ip": []
        }
    },
    "authentication-server": "AD server",
    "description": "",
    "device-server": "None",
    "directory-server": "AD server",
    "dynamic-policy": {
        "dynamic-policy-evaluation": "false",
        "refresh-interval": "60",
        "refresh-policies": "false",
        "refresh-roles": "false"
    },
    "editing-description": "false",
    "inbound-ifmap-attributes": "false",
    "migration-sharing-type": "enable-session-migration",
    "name": "rest-user-realm",
    "role-mapping-rules": {
        "rule": [
            {
                "name": "rest-admin-rule",
                "roles": [
                    "test1"
                ],
                "stop-rules-processing": "false",
                "user-name": {
                    "test": "is",
                    "user-names": [
                        "user1"
                    ]
                }
            }
        ]
    }
}
```

```

    }
  ],
  "user-selects-role": "false",
  "user-selects-roleset": "false"
},
"secondary-authentication-settings": {
  "authentication-must-succeed": "true",
  "name": "-",
  "password-input": "user",
  "predefined-password": "",
  "predefined-user-name": "",
  "user-name-input": "user"
},
"session-migration": "false"
}

```

RESPONSE

HTTP/1.1 201 CREATED

Content-Length: 122

Content-Type: application/json

```

{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or
error!"
      }
    ]
  }
}

```

Deleting a User Realm

To delete a user realm:

REQUEST

```
DELETE /api/v1/configuration/users/user-realms/realm/rest-user-realm HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

```
Content-Length: 0
```

```
Content-Type: application/json
```

Creating a Resource Profile

To create a web resource profile:

REQUEST

```
POST /api/v1/configuration/users/resource-profiles/web-profiles/web-profile/ HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

```
{
  "custom": {
    "bookmarks": {
      "bookmark": [
        {
          "apply": "all",
          "description": "",
          "name": "web-resourceprofile",
          "new-window": "false",
          "no-address-bar": "false",
          "no-tool-bar": "false",
```

```

        "roles": null,
        "url": "http://www.google.com"
    }
]
},
"client-authentication": [],
"java-acl": [],
"rewriting-options": {
    "ptp": [],
    "selective-rewriting": "false",
    "use-jsam": [],
    "use-wsam": []
},
"sso-basic-ntlm-kerberos": [],
"sso-header": [],
"sso-post": [],
"url": "http://www.google.com",
"web-compression": [],
"webacl": [
    {
        "rules": {
            "rule": [
                {
                    "action": "allow",
                    "name": "Allow
http://www.google.com:80/*",
                    "resource":
"http://www.google.com:80/*"
                }
            ]
        }
    }
],
"webcaching": []

```

```

    },
    "description": "",
    "name": "web-resourceprofile",
    "roles": [
        "rest-userrole-3"
    ]
}

```

RESPONSE

```

HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
    "result": {
        "warnings": [
            {
                "message": "The configuration has been
implicitly changed"
            }
        ]
    }
}

```

Deleting a Resource Profile

To delete a web resource profile:

REQUEST

```

DELETE /api/v1/configuration/users/resource-profiles/web-
profiles/web-profile/web-resourceprofile HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Creating a Resource Policy

To create a web resource policy:

REQUEST

```
POST /api/v1/configuration/users/resource-policies/web-policies/web-acls/web-acl/ HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

```
{
  "action": "allow",
  "apply": "selected",
  "description": "",
  "name": "web-acl-policy",
  "parent-type": "none",
  "resources": [
    "1.1.1.1:80,443/*"
  ],
  "roles": [
    "rest-userrole-1"
  ],
  "rules": {
    "rule": []
  }
}
```

RESPONSE

```
HTTP/1.1 201 CREATED
```

```
Content-Length: 122
```

```
Content-Type: application/json
```

```
{
  "result": {
    "info": [
      {
```

```

        "message": "Operation succeed without warning or
error!"
    }
]
}
}

```

Fetching a Resource Policy

To fetch a web resource policy:

REQUEST

```
GET /api/v1/configuration/users/resource-policies/web-policies/web-
acls/web-acl/name=web-acl-policy,parent-type=none HTTP/1.1
```

```
Host: 10.209.113.88
```

```
Authorization: Basic
```

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
```

```
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
Content-Length: 245
```

```
Content-Type: application/json
```

```

{
  "action": "allow",
  "apply": "selected",
  "description": "",
  "name": "web-acl-policy",
  "parent-type": "none",
  "resources": [
    "1.1.1.1:80,443/*"
  ],
  "roles": [
    "rest-userrole-1"
  ],
  "rules": {
    "rule": []
  }
}

```

```

    }
}

```

Deleting a Resource Policy

To delete a web resource policy:

REQUEST

```

DELETE /api/v1/configuration/users/resource-policies/web-
policies/web-acls/web-acl/name=web-acl-policy,parent-type=none
HTTP/1.1

```

Host: 10.209.113.88

Authorization: Basic

MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json

Creating an AD Authentication Server

REQUEST

```

POST /api/v1/configuration/authentication/auth-servers/auth-
server HTTP/1.1

```

Host: 10.209.114.152

Authorization: Basic

QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbc9pdjcrZlRxcz06

Content-Type: application/json

```

{
  "ad": {
    "server-catalog": {
      "custom-variables": {
        "custom-variable": []
      },
      "expressions": {
        "custom-expression": []
      },
      "groups": {
        "ad-group": []
      }
    }
  }
}

```



```

    }
  },
  "settings": {
    "additional-options": {
      "allow-trusted-domains": "false",
      "change-machine-password-after-every": "0",
      "enable-ntlm-protocol": "true",
      "enable-periodic-password-change-of-machine-
account": "false",
      "kerberos": "true",
      "max-domain-connections": "5",
      "ntlm-protocol": "ntlmv2"
    },
    "container-name": "Computers",
    "domain": "TEST",
    "kerberos-realm": "TEST.SAQACERTSERV.COM",
    "nodenames": [
      {
        "computer-name": "0332MWK0NRP111",
        "machine-hardware-id": "0332MOGWK0NRP111S",
        "node": "localhost2"
      }
    ],
    "password-encrypted":
"3u+UR6n8AgABAAAAYCaUPKhCg3J/y46bhB4wz6mnupQH0oTHOTfTexJxP2k=",
    "save-credentials": "true",
    "username": "Administrator"
  }
},
"logical-name": "",
"name": "AD-Server",
"user-record-sync": "false"
}

```

RESPONSE

```

HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
  "warnings": [
  {

```

```

"message": "The configuration has been implicitly changed"
}
    ]
  }
}

```

Deleting an AD Authentication Server

REQUEST

```

DELETE /api/v1/configuration/authentication/auth-servers/auth-
server/AD-Server HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Creating an LDAP Authentication Server

REQUEST

```

POST /api/v1/configuration/authentication/auth-servers/auth-server HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json

```

```

{
  "ldap": {
    "server-catalog": {
      "attributes": {
        "user-attribute": [
          {
            "name": "cn"
          },
          {

```

```

        "name": "department"
      },
      {
        "name": "departmentNumber"
      },
      {
        "name": "employeeNumber"
      },
      {
        "name": "o"
      },
      {
        "name": "ou"
      },
      {
        "name": "sAMAccountName"
      },
      {
        "name": "uid"
      },
      {
        "name": "homeDirectory"
      },
      {
        "name": "homeDrive"
      },
      {
        "name": "wWWHomePage"
      }
    ]
  },
  "custom-variables": {

```

```

        "custom-variable": []
    },
    "expressions": {
        "custom-expression": []
    },
    "groups": {
        "user-group": []
    }
},
"settings": {
    "admin-dn":
"CN=Administrator,CN=Users,DC=test,DC=saqacertserv,DC=com",
    "admin-password-encrypted":
"3u+UR6n8AgABAAAAQkYh+Te/ebXL7gSn+W6IEPOV2YFsaaiKH2SVxkb81TKzWhS1EPFlsNXBpuQP5sW
XfeOYfjmhQSRZ5DP/z9UhQ/116DDne9/u7Lw67HyE/8Q=",
    "attribute-to-update-at-server": "",
    "attribute-type": "type-integer",
    "attribute-value-to-update-at-server": "<LOGINTIMELDAP>",
    "authentication-required-to-search-ldap": "true",
    "backup-port-1": null,
    "backup-port-2": null,
    "backup-server-1": "",
    "backup-server-2": "",
    "connection-timeout": "15",
    "connection-type": "plain",
    "enable-attribute-update-at-server": "false",
    "group-base-dn": "",
    "group-filter": "",
    "ldap-server-type": "active-directory",
    "meetings": {
        "email-address": "mail",
        "full-name": "displayname",
        "name-attribute-mapping": "",
        "user-name": "samaccountname"
    },
    "member-attribute": "",
    "nested-group-level": "0",

```

```

        "port": "389",
        "query-attribute": "",
        "reverse-group-search": "false",
        "search-timeout": "60",
        "server": "10.209.124.88",
        "server-catalog": "catalog",
        "test-user-dn": "",
        "user-base-dn": "DC=test,DC=saqacertserv,DC=com",
        "user-filter": "samaccountname=<USER>",
        "validate-referral-cert": "verifyserverconfigured",
        "validate-server-cert": "false"
    }
},
"logical-name": "",
"name": "LDAP-Server",
"user-record-sync": "false"
}

```

RESPONSE

```

HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}

```

Creating a Radius Server

REQUEST

```

POST /api/v1/configuration/authentication/auth-servers/auth-server
HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json

```

```

{
  "logical-name": "",
  "name": "Radius-Server",
  "radius": {
    "server-catalog": {
      "attributes": {
        "user-attribute": []
      },
      "custom-variables": {
        "custom-variable": []
      },
      "expressions": {
        "custom-expression": []
      }
    },
    "settings": {
      "accounting-port": "1813",
      "authenticate-with-tokens-onetimepassword": "false",
      "authentication-port": "1812",
      "backup-accounting-port": "1813",
      "backup-authentication-port": "1812",
      "backup-server": "10.209.126.179",
      "backup-shared-secret-encrypted":
"3u+UR6n8AgABAAAA2Th1sUV9vXDS9gRdMt1yCB40l6tacMTwhWsTlIFd7Q4=",
      "custom-radius-rules": {
        "custom-radius-rule": []
      },
      "interim-update-interval": null,
      "load-balance-auth": "false",
      "nasid": "",
      "nasipaddr": "10.209.113.88",
      "process-radius-disconnect": "false",
      "retries": "0",
      "server": "10.209.126.179",
      "shared-secret-encrypted":
"3u+UR6n8AgABAAAA2Th1sUV9vXDS9gRdMt1yCB40l6tacMTwhWsTlIFd7Q4=",
      "timeout": "30",
      "use-nc-assigned-ip": "false",
      "use-subsession-interim-update": "false",
      "user-name": "<USER> (<REALM>) [<ROLE SEP=\", \"]"
    }
  }
}

```

```

    }
  },
  "user-record-sync": "false"
}

RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}

```

Modifying Radius Server Details

```

REQUEST
PUT /api/v1/configuration/authentication/auth-servers/auth-server/Radius-Server HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4Nzh1U28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json
{
  "name": "Radius-Server",
  "radius": {
    "settings": {
      "backup-accounting-port": "1814",
      "backup-authentication-port": "1816",
      "backup-server": "2.2.2.2"
    }
  }
}

RESPONSE
HTTP/1.1 200 OK

```

```

Content-Length: 128
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Creating Sign-In-Policy

```

REQUEST

POST /api/v1/configuration/authentication/signin/urls/access-
urls/access-url/ HTTP/1.1

Host: 10.209.113.89

Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06

Content-Type: application/json

{
  "description": "",
  "enabled": "true",
  "page": "Default Sign-In Page",
  "realm-select": "pick-list",
  "url-pattern": "test/url3/",
  "user": {
    "enable-new-ux-pages": "false",
    "meeting-url": "*/meeting/",
    "post-authentication-signin-notification-id": "None",
    "post-authentication-signin-notification-skip": "false",
    "pre-authentication-signin-notification-id": "None",
    "realms": [
      "Users"
    ]
  }
}

```



```

    }
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Deleting Sign-in-Policy

```

REQUEST
DELETE /api/v1/configuration/authentication/signin/urls/access-
urls/access-url/test%5C%2Furl3%5C%2F HTTP/1.1
Host: 10.209.113.89
Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06
Cache-Control: no-cache
RESPONSE
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Disabling Sign-in-URL

```

REQUEST
PUT /api/v1/configuration/authentication/signin/urls/access-
urls/access-url/test%5C%2Furl1%5C%2F/enabled HTTP/1.1

```

```

Host: 10.209.113.89
Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06
Content-Type: application/json
{
  "enabled": "false"
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 128
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}

```

Creating a Web Bookmark for a Role

To create a web bookmark for a role:

```

REQUEST
POST /api/v1/configuration/users/user-roles/user-role/rest-userrole-
1/web/web-bookmarks/bookmark HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json
Cache-Control: no-cache
{
  "auto-allow": "disable",
  "description": "",
  "name": "webbm",

```

```

    "new-window": "false",
    "no-address-bar": "false",
    "no-tool-bar": "false",
    "parent": "--none--",
    "standard": {
        "url": "http://www.yahoo.com"
    }
}

```

RESPONSE

```

HTTP/1.1 201 CREATED
Content-Length: 122
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or
error!"
            }
        ]
    }
}

```

Reordering

For re-ordering existing ordered elements in the configuration, a PUT API can be used with an 'order' suffix. This API can be used to reorder any ordered element in the configuration including role-mapping-rules, resource policies and ACLs.

Example: Reorder existing role-mapping-rules in a specific realm.

REQUEST

```

PUT /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/order HTTP/1.1
Host: 10.209.112.106
Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06
Content-Type: application/json

```

```
{
  "rule": [
    {
      "href": "/api/v1/configuration/users/user-
realms/realm/testRealm/role-mapping-rules/rule/rule3"
    },
    {
      "href": "/api/v1/configuration/users/user-
realms/realm/testRealm/role-mapping-rules/rule/rule1"
    }
  ]
}
```

RESPONSE

HTTP/1.1 200 OK

content-length: 122

content-type: application/json

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or
error!"
      }
    ]
  }
}
```

Fetching the Resource with Multiple Identifiers

Example: Retrieve one of SNMP Trap server configured on PCS device

REQUEST

```
GET /api/v1/configuration/system/log/snmp/localhost2/trap-
servers/trap-server/ip=1.1.1.1,port=162 HTTP/1.1
```

Host: 10.209.112.106

Authorization: Basic

T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkeXmVljc0RtNU14bz06

RESPONSE

```

HTTP/1.1 200 OK
content-length: 65
content-type: application/json
{
  "community": "public",
  "ip": "1.1.1.1",
  "port": "162"
}

```

Updating Resource Identified Using Multiple Identifiers

Example: Updating the community string for specific SNMP trap server identified by IP and port

REQUEST

```

PUT /api/v1/configuration/system/log/snmp/localhost2/trap-
servers/trap-server/ip=1.1.1.1,port=162/community HTTP/1.1
Host: 10.209.112.106
Authorization: Basic
T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkExMVljc0RtNU14bz06
Content-Type: application/json
{
  "community": "pulsesecure"
}

```

RESPONSE

```

HTTP/1.1 200 OK
content-length: 122
content-type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or
error!"
      }
    ]
  }
}

```

```

    }
}

```

Updating Password in Clear Text

Example: Updating password of System Local User.

REQUEST

```

PUT /api/v1/configuration/authentication/auth-servers/auth-server/System%20Local/local/users/user/user0001/password-cleartext
HTTP/1.1

```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkeXmVljc0RtNU14bz06
```

```
Content-Type: application/json
```

```

{
  "password-cleartext": "Psecure"
}

```

RESPONSE

```
HTTP/1.1 200 OK
```

```
content-length: 128
```

```
content-type: application/json
```

```

{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly
changed"
      }
    ]
  }
}

```

```
}

```

Applying Authcode and Downloading Licenses from PCLS on VA-SPE|PSA-V

In PCS 8.3R4|PPS 5.4R4, this REST API can be used to download the license key from PCLS and install on the Virtual Appliance.

REQUEST

```
PUT /api/v1/license/auth-code HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Length: 35
Content-Type: application/json
{
  "auth-code": "<auth-code-to-apply>"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 191
{
  "result": {
    "info": [
      {"message": "Installed new license key \"landmark utility
prestige trip mayor diesel faucet summer prestige income
heritage\""}
    ]
  }
}
```

Applying License

REQUEST

```
PUT /api/v1/license/license-key?action=install HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
{
  "keys": [
```

```

    "key1",
    "key2",
    ...
  ]
}
Example:
{
  "keys": [
    "operation tree crayon holiday kingdom lasso doorway
square dish modem gecko",
    "buffalo safety inch topaz banquet nitrogen garnish step
recital wedge trace"
  ]
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Installed licenses"
      }
    ]
  }
}

```

Deleting License

```

REQUEST
PUT /api/v1/license/license-key?action=delete HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
{
  "keys": [
    "key1",
    "key2",
    ...
  ]
}
Example:
{
  "keys": [

```



```

    "operation tree crayon holiday kingdom lasso doorway
square dish modem gecko",
    "buffalo safety inch topaz banquet nitrogen garnish
step recital wedge trace"
  ]
}

```

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

```

{
  "result": {
    "info": [
      {
        "message": "Deleted <number> licenses"
      }
    ]
  }
}

```

Getting License Clients

REQUEST

GET /api/v1/license/license-clients HTTP/1.1

Host: 10.209.125.7

Authorization: Basic

TnBDUklveFFFQTJKZjM0S2ZxV2JKUlhRaDJJaWGFrYnkvWVpTR3hhNTdmbz0=

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

```

{
  "license_clients": [
    {
      "feature_capacities": [
        {
          "feature_name": "add_user_count",
          "leased_value": 25
        },
        {
          "feature_name": "onboard",
          "leased_value": 0
        },
        {
          "feature_name": "embeddedrdpapplet",

```

```

    "leased_value": 0
  },
  {
    "feature_name": "vm_cores_leasable",
    "leased_value": 4
  },
  {
    "feature_name": "add_meeting_user_count",
    "leased_value": 0
  },
  {
    "feature_name": "cloudsecure_count",
    "leased_value": 0
  },
  {
    "feature_name": "named_user_count",
    "leased_value": 0
  },
  {
    "feature_name": "ueba",
    "leased_value": 0
  }
],
"last_renewal": "Wed, 04 Dec 2019 06:32:26 GMT",
"machine_id": "VASPH3944M9D8551S",
"name": "va_spe_3_3_125_4"
},
{
  "feature_capacities": [
    {
      "feature_name": "add_user_count",
      "leased_value": 25
    },
    {
      "feature_name": "onboard",
      "leased_value": 0
    },
    {
      "feature_name": "embeddedrdpapplet",
      "leased_value": 0
    },
    {
      "feature_name": "vm_cores_leasable",
      "leased_value": 4
    },
    {
      "feature_name": "add_meeting_user_count",
      "leased_value": 0
    }
  ]
}

```

```

    },
    {
      "feature_name": "cloudsecure_count",
      "leased_value": 0
    },
    {
      "feature_name": "named_user_count",
      "leased_value": 0
    },
    {
      "feature_name": "ueba",
      "leased_value": 0
    }
  ],
  "last_renewal": "Thu, 05 Dec 2019 13:45:31 GMT",
  "machine_id": "VASPHXVK2E117PM8S",
  "name": "va_spe_3_3_125_8"
},
]
}

```

Getting License Report from License Server

REQUEST

```

GET /api/v1/license/report HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUklveFFFQTKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 200 OK
{
  <LicenseUsageReport>
    <version>9.1</version>
    <build-number>4748</build-number>
    <time-stamp>Tue Jan 7 10:04:58 2020</time-stamp>
    <MachineId>VASPM79K0BEC8101S</MachineId>
    <cumulative_report>
      <add_user_count>
        <Year id="2020">
          <Month id="Jan">
            <Maximum>648</Maximum>
            <Leased>2200</Leased>
            <Date id="01">
              <Maximum>1</Maximum>
              <Leased>0</Leased>
            </Date>
          </Month>
        </Year>
      </add_user_count>
    </cumulative_report>
  </LicenseUsageReport>
}

```

```

        </Date>
        <Date id="02">
            <Maximum>1</Maximum>
            <Leased>0</Leased>
        </Date>
    </Month>
</Year>
</add_user_count>
<named_user_count>
    <Year id="2020">
        <Month id="Jan">
            <Maximum>0</Maximum>
            <Leased>0</Leased>
            <Date id="01">
                <Maximum>0</Maximum>
                <Leased>0</Leased>
            </Date>
            <Date id="02">
                <Maximum>0</Maximum>
                <Leased>0</Leased>
            </Date>
        </named_user_count>
    <vm_cores_leasable>
        <Year id="2020">
            <Month id="Jan">
                <Maximum>0</Maximum>
                <Leased>0</Leased>
                <Date id="01">
                    <Maximum>0</Maximum>
                    <Leased>0</Leased>
                </Date>
                <Date id="02">
                    <Maximum>0</Maximum>
                    <Leased>0</Leased>
                </Date>
            </vm_cores_leasable>
        <ueba>
            <Year id="2020">
                <Month id="Jan">
                    <Maximum>0</Maximum>
                    <Leased>0</Leased>
                    <Date id="01">
                        <Maximum>0</Maximum>
                        <Leased>0</Leased>
                    </Date>
                    <Date id="02">
                        <Maximum>0</Maximum>
                        <Leased>0</Leased>
                    </Date>
                </Month>
            </Year>
        </ueba>
    </named_user_count>
</vm_cores_leasable>
</ueba>

```

```

        </Date>
    </ueba>
</cumulative_report>
<granular_report>
  <license-client name="node-66" software-version="9.1R4">
    <add_user_count>
      <Year id="2020">
        <Month id="Jan">
          <Maximum>251</Maximum>
          <Leased>500</Leased>
          <Date id="05">
            <Maximum>201</Maximum>
            <Leased>500</Leased>
          </Date>
          <Date id="06">
            <Maximum>251</Maximum>
            <Leased>500</Leased>
          </Date>
          <Date id="07">
            <Maximum>1</Maximum>
            <Leased>500</Leased>
          </Date>
        </Month>
      </Year>
    </add_user_count>
  </license-client>
  <license-client name="node-67" software-version="9.1R4">
    <add_user_count>
      <Year id="2020">
        <Month id="Jan">
          <Maximum>1</Maximum>
          <Leased>500</Leased>
          <Date id="05">
            <Maximum>0</Maximum>
            <Leased>500</Leased>
          </Date>
          <Date id="06">
            <Maximum>1</Maximum>
            <Leased>500</Leased>
          </Date>
          <Date id="07">
            <Maximum>0</Maximum>
            <Leased>500</Leased>
          </Date>
        </Month>
      </Year>
    </add_user_count>
  </license-client>

```

```

</granular_report>
</LicenseUsageReport>
}

```

Exporting TOTP Users from One Device to Another Device

REQUEST

```

GET /api/v1/totp/Google TOTP Auth Server/users HTTP/1.1
Host: 10.209.115.19
Authorization: Basic ZzBPeVdDVmtDT3FoSjBwcVUyRTdzK3hyeHo0OFpzMGtFRjM4WndFNDE1ST06

```

RESPONSE

```

HTTP/1.1 200 OK
Content-Length: 191
Content-Type: application/json
{
  "users": "2lubWxSvAwABAAAAlx9igwcQok9s+MV0zg/b+oer3z
7Kj0iXbVzJ+qDMiguTtWZaxnGHGTGQEChD7BTMGjz1QYb000z
BF+6DGp2y/9pj+8Wf4SXTQbYIEDomT4w2Kl4oc1EZhFruWLW
nll+58x2b0kxsURCb+P0It8K+msqFXBhOEDY7l0W4+P+A8UZ
az6In/gMq8Qd766i7RNloZ+hzHUMYJUB72tzIQ+CiA8tTv6awe
C6TGy9/a9C6vVbLY0+ZUgGTffWzJxcoZbEbdwiCFoZyex5
UWTUFIj0Z4XAPoZ4HTWZsxp5YwXcJpsnbOzCqW/dTB6Wp
YWYp6R+MUn2yu/hZeu7z1qVhXlr8bK5LiFH/u6J76SpErL1eELh1b
YF17DWPfo6xspG7rffhs2k9vPVB1oq2kud+42hPo6vZaMfcwaz9l
KRrftIgAu2o3JBjfdNHrUTOu2+Y6Qmc0in6mFIBNNrVr9D6hdWmIdr
Nr7PXHa4uJoP+CAuOp3OamTox2sgmvE7YNjC0S1SPgyFfx0kfzCb2
K3Mrcq1UuJUJLhK7L3lne4f1QiWkoZ8q8zluaV+eRSJHBez9Pjo+Lz
BpYwoXStduOC20FVY4+KCHDasufdAOCd/Lga4mFFE5ItAui18ObOf
RtxLvoZUIuGS8w019mbRaND1Va52sUzuZBclqx+4lueBCQYEUNrDr
HVG0AzqUBbAeL+WV8VRJrxVW8sIlArqY8n29pD66BozsGKoxBq
XSe/fZxEDu9ZqI4xfzSCCsfgTiv0LAM4p+cZekhcjvRwtuImNjX+qj7A=="
}

```

Importing TOTP Users from One Device to Another Device

REQUEST

```

POST /api/v1/totp/Google TOTP Auth Server/users HTTP/1.1
Host: 10.209.115.19
Authorization: Basic
ZzBPeVdDVmtDT3FoSjBwcVUyRTdzK3hyeHo0OFpzMGtFRjM4WndFNDE1ST06
Content-Type: application/json
{
  "users": "2lubWxSvAwABAAAAlx9igwcQok
9s+MV0zg/b+oer3z7Kj0iXbVzJ+qDMiguTtWZ

```

```

axnGHGTGQEcHD7BTMGjz1QYbO00zBF+6DG
p2y/9pj+8Wf4SXTQbYIeDomT4w2Kl4oc1EZhFru
WLWn1l+58x2b0kxsURCb+P0It8K+msqFXBh
OEDY7l0W4+P+A8UZaz6In/gMq8Qd766i7
RN1oZ+hzHUMYJUB72tzIQ+CiA8tTv6aweC6
TGy9/a9C6vVbLY0+ZUgGTffWzJxcoZbEbdwiCFo
Zyex5UWTUFIj0Z4XAPoZ4HTWZsxP5YwXcJpsnb
OzCqW/dTB6WpYWYp6R+MUn2yu/hZeu7z1qVhXlr8b
K5LifH/u6J76SpErLleELh1bYF17DWPfo6xspG7rffhs2
k9vPVBloq2kud+42hPo6vZaMfcwaz9lKRrftIqAu2o3
JBJfdNhrUTOu2+Y6Qmc0in6MfIBNNrVr9D6hdWmIdr
Nr7PXHa4uJoP+CAuOp3OamTox2sgmvE7YNjC0S1SP
gyFfx0kfzCb2K3Mrcq1UuJUJLhK7L3lne4f1QiWkoZ8q
8zluaV+eRSJHBez9Pjo+LzBpYwoXStduOC20FVY4+KCHD
asufdA OCD/Lga4mFFE5ItAui18ObOfRtxLvoZUIuGS8w019mb
RaND1Va52sUzuZBclqx+4lueBCQYEUNrDrHVG0AzqUBb
AeL+WV8VRJrxVW8sIlArqY8n29pD66BozsGKoxBqXSe/f
ZxEdu9ZqI4xfzSCCsfgTiv0LAM4p+cZekhcvRwtuImNjX+qj7A=="
}

```

RESPONSE

```

HTTP/1.1 200 OK
content-length →47
Content-Type: application/json
{
  "message" => 'Successfully imported user data'
}

```

Sample Error Responses

400 BAD REQUEST

REQUEST

```

PUT /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/rule1 HTTP/1.1
Host: 10.209.112.106
Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrkd5YR3hzVT06
Content-Type: application/json
{
  "name": "rule1",
  "roles": [
    "Users"
  ],

```

```

"stop-rules-processing": "false",
"user-name": {
  "test": "is",
  "user-names": [
    "*"
  ]
}
}

```

RESPONSE

```

HTTP/1.1 400 BAD REQUEST
content-length: 92
content-type: application/json
{
  "message": "The browser (or proxy) sent a request that this
server could not understand."
}

```

Solution: Invalid JSON body content in Request. Please check if JSON is valid.

REQUEST

```

PUT /api/v1/configuration/users/user-roles/user-role/rest-userrole-1
HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNNmemJPbTJxSHI2NVZCdXp5bz06
{
  "name": "rest-userrole-1",
  "web": {
    "web-bookmarks": {
      "bookmark": [
        {
          "auto-allow": "disable",
          "description": "",
          "name": "web-bm-1",
          "new-window": "false",
          "no-address-bar": "false",

```



```

        "no-tool-bar": "false",
        "parent": "--none--",
        "standard": {
            "url": "http://www.yahoo.com"
        }
    ]
},
"web-options": {
    "browsing-untrusted-sslsites": "true",
    "flash-content": "false",
    "hpxproxy-connection-timeout": "1800",
    "http-connection-timeout": "240",
    "java-applets": "true",
    "mask-hostname": "false",
    "persistent-cookies": "false",
    "rewrite-file-urls": "false",
    "rewrite-links-pdf": "false",
    "unrewritten-page-newwindow": "false",
    "user-add-bookmarks": "false",
    "user-enter-url": "false",
    "users-bypass-warnings": "false",
    "warn-certificate-issues": "true",
    "websocket-connection-timeout": "900"
}
}
}

```

RESPONSE

HTTP/1.1 400 BAD REQUEST

Content-Length: 99


Content-Type: application/json

```

{
    "result": {

```

```
    "errors": [  
      {  
        "message": "Accepts only JSON."  
      }  
    ]  
  }  
}
```

 **Note:** Include the “Content-Type” header in the request with a value “application/json” as used in the examples above.

403 Forbidden

REQUEST

```
GET /api/v1/auth HTTP/1.1  
Host: 10.209.112.106  
Authorization: Basic YWRtaW5kYjpkYW5hMTIz  
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 403 Forbidden  
cache-control: no-store  
connection: Keep-Alive  
content-type: text/html; charset=utf-8  
expires:-1  
keep-alive: timeout=15  
strict-transport-security max-age=31536000  
transfer-encoding: chunked
```

Solutions:

1. Make sure admin user used for authentication has "Allow access to REST APIs" option enabled from admin UI
2. Admin Username and Password passed in Authorization header are correct
3. If api_key is available, use api_key value as username and password as empty in authorization header

404 NOT FOUND

REQUEST

```
GET /api/v1/configuration/users/user-realms/realm/testRealm/role-  
mapping-rules/rule HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06
```

RESPONSE

```
HTTP/1.1 404 NOT FOUND
```

```
content-length: 213
```

```
content-type: application/json
```

```
{  
  "result": {  
    "errors": [  
      {  
        "message": "Invalid resource path; use  
\"users/user-realms/realm/testRealm/role-mapping-  
rules/rule/<resource-id>\" to access a specific resource"  
      }  
    ]  
  }  
}
```

Solution: Resource-id should be passed in Resource path as shown in example below.

REQUEST

```
GET /api/v1/configuration/users/user-realms/realm/testRealm/role-  
mapping-rules/rule/rule1 HTTP/1.1
```

```
Host: 10.209.112.106
```

```
Authorization: Basic
```

```
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06
```

RESPONSE

```
HTTP/1.1 200 OK
```

```
content-length: 167
```

```
content-type: application/json
```

```
{  
  "name": "rule1",
```

```

"roles": [
  "Users"
],
"stop-rules-processing": "false",
"user-name": {
  "test": "is",
  "user-names": [
    "*"
  ]
}
}

```

Solution: Invalid JSON body content in Request. Please check if JSON is valid.

422 UNPROCESSABLE ENTITY

REQUEST

POST /api/v1/configuration/users/user-realms/realm/testRealm/role-mapping-rules/rule/ HTTP/1.1

Host: 10.209.112.106

Authorization: Basic

Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06

Content-Type: application/json

```

{
  "name": "rule2",
  "roles": [
    "Users",
    "testRole1"
  ],
  "stop-rules-processing": "false",
  "user-name": {
    "test": "is",
    "user-names": [
      "user1"
    ]
  ]
}

```

```

    }
}
RESPONSE
HTTP/1.1 422 UNPROCESSABLE ENTITY
content-length: 368
content-type: application/json
{
  "result": {
    "errors": [
      {
        "message": "[/users/user-
realms/realm[name=testRealm]/role-mapping-
rules/rule[name=rule2]/roles] Invalid reference: no 'User Roles'
object found with identifier 'testRole1'."
      },
      {
        "message": "Failed to resolve path references"
      },
      {
        "message": "Commit failed"
      }
    ]
  }
}

```

Solution: Make sure to have all the referenced resources are created first using POST call and then repeat.

Limitations

1. Configuration of large data objects is not qualified- ESAP, Pulse Client package, Custom Sign-in page, applets, and so on.
2. Resource names similar to resource tags e.g. vlans, roles, etc. should be avoided while creating new resources.

PPS-Specific Configurations Using REST APIs

- Creating the HC Policy
- Deleting the HC Policy
- Creating the Infranet Enforcer
- Deleting the Infranet Enforcer
- Creating a Resource Policy
- Deleting a Resource Policy
- Creating a RADIUS Client
- Deleting a RADIUS Client
- Creating a RADIUS Attribute Policy
- Deleting a RADIUS Attribute Policy
- Creating SNMP Device
- Deleting SNMP Device
- Creating SNMP Policy
- Deleting SNMP Policy
- Creating Device Group - TACACS+
- Deleting Device Group- TACACS+
- Creating TACACS+ Client
- Deleting TACACS+ Client
- Creating Shell Policies
- Deleting Shell Policies
- Creating Admission Control Client
- Deleting Admission Control Client
- Creating Admission Control Policy
- Deleting Admission Control Policy
- Profiler REST APIs

Creating the HC Policy

REQUEST

```

POST api/v1/configuration/authentication/endpoint/host-
checker/policies/policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVks5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "policy-name": "HC",
  "regular": {
    "platforms": {
      "chromeos": {
        "dashboard": {
          "consider-for-reporting": "true"
        },
        "remediation": {
          "custom-instructions": "",
          "enable-custom-instructions": "false",
          "send-reason-strings": "true"
        }
      },
      "windows": {
        "dashboard": {
          "consider-for-reporting": "true"
        },
        "remediation": {
          "custom-instructions": "",
          "delete-files": "false",
          "enable-custom-instructions": "false",
          "files": null,
          "kill-processes": "false",
          "processes": null,
          "send-reason-strings": "true"
        },
        "rule-expression": {
          "custom-expression": "",
          "requirement": "all"
        },
        "rules": {
          "advancedRule": [],
          "firewall-rules": {
            "firewall-rule": [
              {
                "needs-monitoring": "false",
                "product-list": null,
                "product-selection-option":
"specific",
                "rule-name": "rule1",
                "select-specific-product": "false",
                "select-specific-vendor": "true",
                "selected-product-list": {
                  "product-info": [
                    {
                      "product-name":
"Windows Firewall (10.x)",
                      "turn-on-firewall":
"true"
                    }
                  ]
                }
              }
            ]
          }
        }
      }
    }
  }
}

```


Creating the Infranet Enforcer

REQUEST

```
POST api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "idp-for-local-sessions-only": "true",
  "junos": {
    "location-group": "- No 802.1X -",
    "password-encrypted":
"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
  },
  "name": "SRX",
  "serial-number": [
    "ABCNWPWFS"
  ],
  "severity-filter": "medium",
  "use-idp": "false"
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}
```

Deleting the Infranet Enforcer

REQUEST

```
DELETE api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer/SRX HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating a Resource Policy

REQUEST

```
POST api/v1/configuration/uac/infranet-enforcer/resource-access-
policies/resource-access-policy/ HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "action": "allow-access",
  "apply": "all-roles",
  "apply-ie-options": "all-options",
  "deny-message": "",
  "description": "",
  "ie-options": [],
  "infranet-enforcer": [
    "(all)"
  ],
  "name": "Resource Policy",
  "resources": [
    "10.25.15.0/24:*"
  ],
  "roles": null,
  "vsys": ""
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}
```

Deleting a Resource Policy

REQUEST

```
DELETE api/v1/configuration/uac/infranet-enforcer/resource-access-
policies/resource-access-policy/Resource%20Policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating a RADIUS Client

REQUEST

```
POST /api/v1/configuration/uac/network-access/radius-clients/radius-
client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "coa-support": "false",
  "description": "",
  "disconnect-support": "true",
  "dynamic-auth-port": "3799",
  "enable": "true",
  "gatewayid": "",
  "ip-address": "10.204.88.12",
  "ip-address-range": "1",
  "kek-encrypted": "",
  "key-wrap-format": "HEX",
  "key-wrap-support": "false",
  "location-group": "Default",
  "mack-encrypted": "",
  "make-model": "Ruckus Wireless",
  "name": "Ruckus",
  "ruckus-certificate-verification": "false",
  "ruckus-password-encrypted": "",
  "shared-secret-encrypted":
"3u+UR6n8AgABAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}
```

Deleting a RADIUS Client

REQUEST

```
Delete /api/v1/configuration/uac/network-access/radius-clients/radius-
client/Ruckus HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating a RADIUS Attribute Policy

REQUEST

```
POST /api/v1/configuration/uac/network-access/radius-attribute/radius-attributes-policies/radius-attribute-policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "apply": "all",
  "description": "",
  "location-group": [
    "Guest"
  ],
  "name": "Return Attribute policy",
  "network-interface": "automatic",
  "open-port": "false",
  "return-attribute-flag": "false",
  "return-attributes": {
    "return-attribute": []
  },
  "roles": null,
  "send-session-timeout-by-default": "false",
  "send-termination-action-by-default": "false",
  "vlan": "65",
  "vlan-check": "true"
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

Deleting a RADIUS Attribute Policy

REQUEST

```
DELETE /api/v1/configuration/uac/network-access/radius-attribute/radius-attributes-policies/radius-attribute-policy/Return%20Attribute%20policy/HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

```
Content-Length: 0
Content-Type: application/json
```

Creating SNMP Device

REQUEST

```
POST /api/v1/configuration/uac/snmpEnforcement/clients/client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "default-vlan": "0",
  "description": "",
  "enable": "true",
  "ip-address": "10.204.88.12",
  "location-group": "none",
  "model": "Ruckus Wireless",
  "name": "ruckus",
  "read-auth-password-encrypted": "",
  "read-auth-protocol": "md5",
  "read-priv-password-encrypted": "",
  "read-priv-protocol": "",
  "read-security-level": "auth",
  "read-username": "public",
  "snmp-enforcement": "false",
  "snmp-version": "V2",
  "ssh-passphrase-encrypted": "",
  "ssh-port-number": "22",
  "ssh-private-key-encrypted": "",
  "ssh-user-name": "",
  "ssh-user-password-encrypted": "",
  "sys-contact": "https://support.ruckuswireless.com/contact_us",
  "sys-description": "Ruckus Wireless ZD1200",
  "sys-location": "350 West Java Dr. Sunnyvale, CA 94089 US",
  "sys-name": "ruckus",
  "trap-auth-password-encrypted": "",
  "trap-auth-protocol": "md5",
  "trap-priv-password-encrypted": "",
  "trap-priv-protocol": "",
  "trap-security-level": "auth",
  "trap-username": "public",
  "use-samecredential": "true",
  "write-auth-password-encrypted": "",
  "write-auth-protocol": "md5",
  "write-priv-password-encrypted": "",
  "write-priv-protocol": "",
  "write-security-level": "auth",
  "write-username": "public"
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
```

```
error!"
    }
  ]
}
}
```

Deleting SNMP Device

REQUEST

```
DELETE
/api/v1/configuration/uac/snmpEnforcement/clients/client/ruckus/HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating SNMP Policy

REQUEST

```
POST /api/v1/configuration/uac/snmpEnforcement/snmpPolicies/policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "apply-to-roles": "selected",
  "description": "",
  "location-group": "Guest Wired",
  "name": "SNMP policy",
  "roles": [
    "Guest Wired Restricted"
  ],
  "vlan": "65"
}
```

RESPONSE

```
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or
error!"
      }
    ]
  }
}
```

```
}
```

Deleting SNMP Policy

REQUEST

```
DELETE
/api/v1/configuration/uac/snmpEnforcement/snmpPolicies/policy/SNMP%20policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating Device Group - TACACS+

REQUEST

```
POST /api/v1/configuration/uac/networkDeviceAdministration/groups/group/
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

```
{
  "admin-realm": "Admin Users",
  "description": "",
  "name": "Device Group"
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

Deleting Device Group- TACACS+

REQUEST

```
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/groups/group/Device%20Group
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE


```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating TACACS+ Client

REQUEST

```
POST /api/v1/configuration/uac/networkDeviceAdministration/clients/client
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "description": "",
  "deviceGroup": "Device Group",
  "enable": "true",
  "ipAddress": "10.204.88.244",
  "ipAddressRange": "1",
  "name": "TACACS client",
  "shared-secret-encrypted":
  "3u+UR6n8AgABAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
}
```

RESPONSE

```
{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}
```

Deleting TACACS+ Client

REQUEST

```
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/clients/client/TACACS
%20client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating Shell Policies

REQUEST

```
POST /api/v1/configuration/uac/networkDeviceAdministration/policies/policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "apply-action": "deny",
  "apply-groups": "all",
  "apply-roles": "all",
  "commandSets": {
    "command-set": []
  },
  "defaultPrivilege": "1",
  "description": "",
  "groups": null,
  "maxPrivilege": "1",
  "name": "TACACS policy",
  "roles": null
}
```

RESPONSE

```
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

Deleting Shell Policies

REQUEST

```
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/policies/policy/TACACS%20policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

RESPONSE

```
{
  "result": {
    "warnings": [
      {

```

```

      "message": "The configuration has been implicitly changed"
    }
  ]
}

```

Creating Admission Control Client

REQUEST

```

POST /api/v1/configuration/uac/admissionControl/clients/client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "description": "",
  "enable": "true",
  "ipAddress": "10.204.88.12",
  "name": "FORTINET",
  "templateID": "fortigate-text.itmpl"
}

```

RESPONSE

```

{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}

```

Deleting Admission Control Client

REQUEST

```

DELETE /api/v1/configuration/uac/admissionControl/clients/client/FORTINET HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Creating Admission Control Policy

REQUEST

```

POST /api/v1/configuration/uac/admissionControl/policies/policy/ HTTP/1.1
Host xx.xx.xx.xx

```

```

Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "action": "ignore",
  "apply": "selected",
  "count": "1",
  "event": "utm:ips",
  "name": "policy1",
  "replacementRole": null,
  "replacementType": "Permanent",
  "roles": null,
  "severity": "critical",
  "templateID": "fortigate-text.itmpl"
}

```

RESPONSE

```

{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}

```

Deleting Admission Control Policy

REQUEST

```

DELETE /api/v1/configuration/uac/admissionControl/policies/policy/policy1 HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json

```

RESPONSE

```

HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json

```

Profiler REST APIs

Approving Devices

REQUEST

```

PUT api/v1/profiler/endpoints/simplified/xx:xx:xx:xx:xx:xx HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "status": "approved"
}

```

RESPONSE

```

HTTP/1.1 200 OK

```

```
Content-Type: application/json
{
  "Successfully updated."
}
```

Updating Device Attributes

REQUEST

```
PUT api/v1/profiler/endpoints/simplified/xx:xx:xx:xx:xx:xx HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic VU9qSTlGTzNrYVks5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
  "manufacturer": "Windows",
  "os": "Windows"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "Successfully updated."
}
```